

Round cylinder ESNU-50- -

Part number: 194004

FESTO



Data sheet

Feature	Value
Stroke	1 mm...50 mm
Piston diameter	50 mm
Cushioning	Elastic cushioning rings/pads at both ends
Mounting position	Any
Structural design	Piston Piston rod Cylinder barrel
Position sensing	Via proximity switch
Variants	Weld spatter protection Extended external thread piston rod Internal thread on piston rod Special thread on piston rod Piston rod with external hexagon Low friction for balancer applications Additional PTFE piston guide
Operating pressure	0.12 MPa...1 MPa 1.2 bar...10 bar
Mode of operation	Pushing Single-acting
Operating medium	Compressed air as per ISO 8573-1:2010 [7:4:4]
Information on operating and pilot media	Operation with oil lubrication possible (required for further use)
Corrosion resistance class (CRC)	2 - Moderate corrosion stress
LABS (PWIS) conformity	VDMA24364-B1/B2-L
Ambient temperature	-20 °C...120 °C
Impact energy in the end positions	1 J
Theoretical force at 6 bar, advancing	976 N...1011 N
Moving mass at 0 mm stroke	413 g
Additional moving mass per 10 mm stroke	25 g
Basic weight with 0 mm stroke	1087 g
Additional weight per 10 mm stroke	40 g
Type of mounting	With accessories
Pneumatic connection	G1/4
Note on materials	RoHS compliant
Cover material	Wrought aluminum alloy

Feature	Value
Seals material	NBR TPE-U(PU)
Piston rod material	High-alloy steel
Material of cylinder barrel	high-alloy stainless steel