



# Motor cable NEBM-M23G15-EH-5-Q10N-R3LEG14

Part number: 5251389

**FESTO**



## Data sheet

| Feature                                        | Value                      |
|------------------------------------------------|----------------------------|
| Based on norm                                  | EN 61984                   |
| Cable designation                              | Without label holder       |
| Product weight                                 | 2250 g                     |
| Electrical connection 1, function              | Field device side          |
| Electrical connection 1, design                | Round                      |
| Electrical connection 1, connection type       | Hybrid socket              |
| Electrical connection 1, cable outlet          | Straight                   |
| Electrical connection 1, connection technology | M23x1                      |
| Electrical connection 1, number of pins/wires  | 15                         |
| Electrical connection 1, occupied pins/wires   | 12                         |
| Electrical connection 1, type of mounting      | Screw-type lock            |
| Electrical connection 2, function              | Control side               |
| Electrical connection 2, connection type       | Connector and cable        |
| Electrical connection 2, cable outlet          | Straight                   |
| Electrical connection 2, connection technology | RJ45 and open end          |
| Electrical connection 2, number of pins/wires  | 14                         |
| Electrical connection 2, occupied pins/wires   | 12                         |
| DC operating voltage range                     | 0 V...850 V                |
| Operating voltage range AC                     | 0 V...630 V                |
| Current rating at 40° C                        | 23.7 A                     |
| Surge resistance                               | 6 kV                       |
| Shield                                         | Yes                        |
| Cable length                                   | 5 m                        |
| Cable characteristic                           | Suitable for energy chains |
| Connector cable test conditions                | Test conditions on request |
| Bending radius, fixed cable installation       | 55.6 mm                    |
| Bending radius, flexible cable installation    | 97.3 mm                    |
| Cable diameter                                 | 13.9 mm                    |
| Cable diameter tolerance                       | ± 0.3 mm                   |

| Feature                                              | Value                                                                                                                     |
|------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------|
| Cable design                                         | 4 x 2.5 mm <sup>2</sup> + 1 x (2 x 1.0 mm <sup>2</sup> ) + 1 x (2 x 0.24 mm <sup>2</sup> + 2 x 2 x 0.15 mm <sup>2</sup> ) |
| Nominal conductor cross section                      | 0.15 mm <sup>2</sup><br>0.24 mm <sup>2</sup><br>1 mm <sup>2</sup><br>2.5 mm <sup>2</sup>                                  |
| Wire ends                                            | Wire ferrule                                                                                                              |
| Degree of protection                                 | IP67                                                                                                                      |
| Note on degree of protection                         | In mounted state                                                                                                          |
| Ambient temperature                                  | -40 °C...90 °C                                                                                                            |
| Ambient temperature with flexible cable installation | -25 °C...80 °C                                                                                                            |
| CE marking (see declaration of conformity)           | As per EU low voltage directive<br>As per EU RoHS directive                                                               |
| UKCA marking (see declaration of conformity)         | To UK RoHS instructions<br>To UK instructions for electrical equipment                                                    |
| LABS (PWIS) conformity                               | VDMA24364-B2-L                                                                                                            |
| Note on materials                                    | RoHS compliant<br>Halogen-free                                                                                            |
| Contamination level                                  | 3                                                                                                                         |
| Corrosion resistance class (CRC)                     | 1 - Low corrosion stress                                                                                                  |
| Material of cable sheath                             | TPE-U(PUR)                                                                                                                |
| Color cable sheath                                   | Gray                                                                                                                      |
| Insulating sheath material                           | PP                                                                                                                        |