

# Rotary distributor GF-1/4

Part number: 2094

**FESTO**



## Data sheet

| Feature                                         | Value                                                              |
|-------------------------------------------------|--------------------------------------------------------------------|
| Nominal width                                   | 11.5 mm                                                            |
| Mounting position                               | Any                                                                |
| Operating pressure for entire temperature range | -0.095 MPa...1 MPa<br>-0.95 bar...10 bar<br>-13.775 psi...145 psi  |
| Standard flow rate 1-2.1 (6->0)                 | 2932 l/min                                                         |
| Standard flow rate 1-2.X open (6->0)            | 2977 l/min                                                         |
| Standard nominal flow rate 1.1-2.1              | 1792 l/min                                                         |
| Max. rotational speed                           | 300 rpm                                                            |
| Operating medium                                | Compressed air as per ISO 8573-1:2010 [7:::]                       |
| Information on operating and pilot media        | Operation with oil lubrication possible (required for further use) |
| LABS (PWIS) conformity                          | VDMA24364-B1/B2-L                                                  |
| Temperature of medium                           | -10 °C...60 °C                                                     |
| Ambient temperature                             | -10 °C...60 °C                                                     |
| Product weight                                  | 250 g                                                              |
| Pneumatic connection 1                          | External thread G1/4                                               |
| Pneumatic connection 2                          | Internal thread G1/4                                               |
| Note on materials                               | RoHS compliant                                                     |
| Housing material                                | Wrought aluminum alloy                                             |
| Shaft material                                  | High-alloy steel                                                   |