

# Manifold sub-base VABV-S1-1HSB-N38

Part number: 8030651

**FESTO**



## Data sheet

| Feature                                  | Value                                                              |
|------------------------------------------|--------------------------------------------------------------------|
| Width                                    | 44 mm                                                              |
| Exhaust air function                     | Adjustable                                                         |
| Based on norm                            | ISO 5599-1                                                         |
| Max. no. of valve positions              | 1                                                                  |
| Operating pressure                       | -0.09 MPa...1 MPa<br>-0.9 bar...10 bar                             |
| Suitability for vacuum                   | Yes                                                                |
| Operating medium                         | Compressed air as per ISO 8573-1:2010 [7:4:4]                      |
| Information on operating and pilot media | Operation with oil lubrication possible (required for further use) |
| Corrosion resistance class (CRC)         | 0 - No corrosion stress                                            |
| LABS (PWIS) conformity                   | VDMA24364-B1/B2-L                                                  |
| Storage temperature                      | -20 °C...60 °C                                                     |
| Temperature of medium                    | -10 °C...50 °C                                                     |
| Pilot medium                             | Compressed air as per ISO 8573-1:2010 [7:4:4]                      |
| Ambient temperature                      | -10 °C...50 °C                                                     |
| Product weight                           | 490 g                                                              |
| Pneumatic connection 2                   | 3/8 NPT                                                            |
| Pneumatic connection 4                   | 3/8 NPT                                                            |
| Note on materials                        | RoHS compliant                                                     |
| Material of sub-base                     | Die-cast aluminum                                                  |