


One-way flow control valve CRGRLA-1/8-B

Part number: 161404

FESTO



Data sheet

Feature	Value
Valve function	One-way flow control function
Pneumatic connection 1	G1/8
Pneumatic connection 2	G1/8
Actuation type	Manual
Adjusting element	Slotted screw
Type of mounting	Screw-in
Standard nominal flow rate in flow control direction	340 l/min
Standard nominal flow rate in non-return direction	260 l/min...420 l/min
Operating pressure	0.03 MPa...1 MPa 0.3 bar...10 bar 4.35 psi...145 psi
Ambient temperature	-20 °C...80 °C
Maritime classification	See certificate
Explosion prevention and protection	Observe the information on the certificate Zone 1 (ATEX) Zone 2 (ATEX) Zone 21 (ATEX) Zone 22 (ATEX)
Mounting position	Any
Rotatability	360 deg/continuous swiveling not permissible
Standard flow rate in flow control direction 6 -> 0 bar	580 l/min
Standard flow rate in non-return direction at 6 -> 0 bar	530 l/min...590 l/min
Operating medium	Compressed air as per ISO 8573-1:2010 [7:4:4]
Information on operating and pilot media	Operation with oil lubrication possible (required for further use)
LABS (PWIS) conformity	VDMA24364-B2-L
Suitability for the production of Li-ion batteries	Suitable for battery production with reduced Cu/Zn/Ni values (F1a)
Cleanroom suitability, measured according to ISO 14644-14	Class 4 according to ISO 14644-1
Storage temperature	-10 °C...40 °C

Feature	Value
For use in the food industry	See supplementary material information
Temperature of medium	-10 °C...60 °C
Nominal width	4 mm
Max. tightening torque	6 Nm
Permissible actuation moment, adjusting screw	0.5 Nm
Product weight	37.8 g
Note on materials	RoHS compliant
Seals material	FPM PVC
Hollow bolt material	High-alloy steel
Material of adjusting screw	high-alloy stainless steel
Swivel joint material	high-alloy stainless steel