


# Quick exhaust valve SEU-1/8

Part number: 4616

**FESTO**



## Data sheet

| Feature                                            | Value                                                              |
|----------------------------------------------------|--------------------------------------------------------------------|
| Valve function                                     | Quick exhaust                                                      |
| Selection of additional function                   | with muffler                                                       |
| Pneumatic connection 1                             | G1/8                                                               |
| Pneumatic connection 2                             | G1/8                                                               |
| Type of mounting                                   | Screw-in                                                           |
| Standard nominal flow rate exhaust air 6->5 bar    | 550 l/min                                                          |
| Standard flow rate exhaust 6-> 0 bar               | 1000 l/min                                                         |
| Standard nominal flow rate pressurization 6->5 bar | 300 l/min                                                          |
| Operating pressure                                 | 0.5 bar...10 bar                                                   |
| Ambient temperature                                | -20 °C...75 °C                                                     |
| Housing material                                   | Die-cast zinc                                                      |
| Operating medium                                   | Compressed air as per ISO 8573-1:2010 [7:4:4]                      |
| Nominal width                                      | 5 mm                                                               |
| Mounting position                                  | Any                                                                |
| Information on operating and pilot media           | Operation with oil lubrication possible (required for further use) |
| LABS (PWIS) conformity                             | VDMA24364-B1/B2-L                                                  |
| Temperature of medium                              | -20 °C...75 °C                                                     |
| Noise level                                        | 85 dB(A)                                                           |
| Product weight                                     | 65 g                                                               |
| Seals material                                     | NBR                                                                |