



Shut-off valve HE-3A-3/8-QS-5/16-U

Part number: 190874

FESTO



Data sheet

Feature	Value
Valve function	3/2-way, bistable
Selection of additional function	with exhaust function
Pneumatic connection 1	QS-5/16
Pneumatic connection 2	3/8 NPT
Actuation type	Manual
Type of mounting	Alternatively: Direct mounting via through-hole Direct fastening via thread
Normal nominal flow rate (normalized to DIN 1343)	478.8 l/min
Nominal width	3.6 mm
Operating pressure	-0.095 MPa...1 MPa -0.95 bar...10 bar
Ambient temperature	0 °C...60 °C
Housing material	PBT-reinforced
Operating medium	Compressed air as per ISO 8573-1:2010 [7:::]
Exhaust air function	Cannot be throttled
Sealing principle	Soft
Mounting position	Any
Structural design	Piston gate valve
Type of control	directly
Flow direction	Non-reversible
Information on operating and pilot media	Operation with oil lubrication possible (required for further use)
Corrosion resistance class (CRC)	2 - Moderate corrosion stress
LABS (PWIS) conformity	VDMA24364-B2-L
Cleanroom suitability, measured according to ISO 14644-14	Class 4 according to ISO 14644-1
Temperature of medium	0 °C...60 °C
Product weight	48 g
Pneumatic connection 3	Not ducted
Note on materials	RoHS compliant
Seals material	NBR