

# Push-in T-connector QST-V0-6

Part number: 160533

**FESTO**



## Data sheet

| Feature                                         | Value                                                                    |
|-------------------------------------------------|--------------------------------------------------------------------------|
| Size                                            | Standard                                                                 |
| Nominal width                                   | 4.8 mm                                                                   |
| Material fire test                              | UL94 V-0 (housing)<br>UL94 V-0 (releasing ring)                          |
| Design                                          | T-shape                                                                  |
| Pack size                                       | 10                                                                       |
| Structural design                               | Push-pull principle                                                      |
| Operating pressure for entire temperature range | -0.095 MPa...1 MPa<br>-0.95 bar...10 bar<br>-13.775 psi...145 psi        |
| Information on operating pressure               | Water: max. 0.6 MPa at max. 50 °C                                        |
| Operating medium                                | Compressed air as per ISO 8573-1:2010 [7::-]<br>Water (liquid, ice-free) |
| Information on operating and pilot media        | Lubricated operation possible                                            |
| Corrosion resistance class (CRC)                | 2 - Moderate corrosion stress                                            |
| LABS (PWIS) conformity                          | VDMA24364-B1/B2-L                                                        |
| Ambient temperature                             | 0 °C...60 °C                                                             |
| Product weight                                  | 14 g                                                                     |
| Pneumatic connection 1                          | For pneumatic tubing outside diameter 6 mm                               |
| Pneumatic connection 2                          | for pneumatic tubing outside diameter 6 mm                               |
| Releasing ring color                            | Black                                                                    |
| Note on materials                               | RoHS compliant                                                           |
| Housing material                                | PBT                                                                      |
| Releasing ring material                         | PBT                                                                      |
| Material of tubing seal                         | NBR                                                                      |
| Material of tube retaining claw                 | high-alloy stainless steel<br>Brass                                      |