


# Mini slide DGST-16-100-PA

Part number: 8085136

**FESTO**



## Data sheet

| Feature                                                   | Value                                                              |
|-----------------------------------------------------------|--------------------------------------------------------------------|
| Stroke                                                    | 100 mm                                                             |
| Adjustable end-position range/front length                | 22.8 mm                                                            |
| Adjustable end-position range/rear length                 | 21.5 mm                                                            |
| Piston diameter                                           | 16 mm                                                              |
| Drive unit operating mode                                 | Yoke                                                               |
| Cushioning                                                | Elastic cushioning rings/pads at both ends                         |
| Mounting position                                         | Any                                                                |
| Guide                                                     | Recirculating ball bearing                                         |
| Structural design                                         | Double piston<br>Yoke<br>Piston rod<br>Slide                       |
| Position sensing                                          | Via proximity switch                                               |
| Operating pressure                                        | 0.1 MPa...0.8 MPa<br>1 bar...8 bar<br>14.5 psi...116 psi           |
| Max. speed                                                | 0.8 m/s                                                            |
| Repetition accuracy                                       | <= 0.3 mm                                                          |
| Mode of operation                                         | Double-acting                                                      |
| Operating medium                                          | Compressed air as per ISO 8573-1:2010 [7:4:4]                      |
| Information on operating and pilot media                  | Operation with oil lubrication possible (required for further use) |
| Corrosion resistance class (CRC)                          | 1 - Low corrosion stress                                           |
| LABS (PWIS) conformity                                    | VDMA24364-B1/B2-L                                                  |
| Cleanroom suitability, measured according to ISO 14644-14 | Class 6 according to ISO 14644-1                                   |
| Ambient temperature                                       | -10 °C...60 °C                                                     |
| Impact energy in the end positions                        | 0.25 J                                                             |
| Cushioning length                                         | 1 mm                                                               |
| Max. force Fy                                             | 940 N                                                              |
| Max. force Fz                                             | 940 N                                                              |
| Max. torque Mx                                            | 12 Nm                                                              |
| Max. torque My                                            | 10 Nm                                                              |
| Max. torque Mz                                            | 10 Nm                                                              |

| Feature                                | Value                            |
|----------------------------------------|----------------------------------|
| Theoretical force at 6 bar, retracting | 207 N                            |
| Theoretical force at 6 bar, advancing  | 241 N                            |
| Moving mass                            | 556 g                            |
| Product weight                         | 1142 g                           |
| Type of mounting                       | With through-hole                |
| Pneumatic connection                   | M5                               |
| Note on materials                      | RoHS compliant                   |
| Cover material                         | Wrought aluminum alloy           |
| Seals material                         | HNBR                             |
| Guide material                         | POM<br>TPE-E<br>High-alloy steel |
| Housing material                       | Wrought aluminum alloy           |
| Piston rod material                    | high-alloy stainless steel       |