

**Cover kit**  
**VAVC-F12-SCC-25-P**  
 Part number: 8201223

**FESTO**



**Data sheet**

| Feature                             | Value                                                                                                                                                |
|-------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| Nominal width DN                    | 25                                                                                                                                                   |
| Explosion prevention and protection | Zone 1 (ATEX)<br>Zone 2 (ATEX)<br>Zone 21 (ATEX)<br>Zone 22 (ATEX)                                                                                   |
| LABS (PWIS) conformity              | VDMA24364 Zone III                                                                                                                                   |
| Medium                              | Vapor<br>Hydraulic fluid based on mineral oil<br>Inert gas<br>Mineral oil<br>Water<br>Filtered compressed air, 200 µm filter mesh<br>Neutral liquids |
| Information on medium               | Gaseous media are only permitted with inflow via valve seat.                                                                                         |
| Temperature of medium               | 100 °C...230 °C                                                                                                                                      |
| Ambient temperature                 | 0 °C...60 °C                                                                                                                                         |
| Storage temperature                 | -10 °C...60 °C                                                                                                                                       |
| Mounting position                   | Any                                                                                                                                                  |
| Product weight                      | 921 g                                                                                                                                                |
| Note on materials                   | RoHS compliant                                                                                                                                       |
| Cover material                      | high-alloy stainless steel                                                                                                                           |
| Spindle seal material               | PTFE                                                                                                                                                 |
| Seat seal material                  | PEEK                                                                                                                                                 |