


# Selector valve VHEF-E-M52-M-G18

Part number: 8080972

**FESTO**



## Data sheet

| Feature                                           | Value                                                              |
|---------------------------------------------------|--------------------------------------------------------------------|
| Valve function                                    | 5/2-way, monostable                                                |
| Actuation type                                    | Manual                                                             |
| Width                                             | 20 mm                                                              |
| Normal nominal flow rate (normalized to DIN 1343) | 750 l/min                                                          |
| Pneumatic working port                            | G1/8                                                               |
| Operating pressure                                | -0.095 MPa...1 MPa<br>-0.95 bar...10 bar                           |
| Structural design                                 | Piston gate valve                                                  |
| Reset method                                      | Mechanical spring                                                  |
| Nominal width                                     | 5.2 mm                                                             |
| Exhaust air function                              | Adjustable                                                         |
| Application note                                  | Only operate by hand                                               |
| Sealing principle                                 | Soft                                                               |
| Mounting position                                 | Any                                                                |
| Type of control                                   | directly                                                           |
| Flow direction                                    | Reversible                                                         |
| Lap                                               | Positive overlap                                                   |
| Max. switching frequency                          | 0.5 Hz                                                             |
| Explosion prevention and protection               | Zone 1 (ATEX)<br>Zone 2 (ATEX)<br>Zone 21 (ATEX)<br>Zone 22 (ATEX) |
| Operating medium                                  | Compressed air as per ISO 8573-1:2010 [7:::-]                      |
| Information on operating and pilot media          | Operation with oil lubrication possible (required for further use) |
| Corrosion resistance class (CRC)                  | 1 - Low corrosion stress                                           |
| LABS (PWIS) conformity                            | VDMA24364-B1/B2-L                                                  |
| Temperature of medium                             | -10 °C...60 °C                                                     |
| Ambient temperature                               | -10 °C...60 °C                                                     |
| Actuating torque                                  | 0.3 Nm                                                             |
| Max. force on actuator                            | 200 N                                                              |
| Max. transverse load on actuator                  | 200 N                                                              |
| Product weight                                    | 235 g                                                              |
| Type of mounting                                  | Alternatively:                                                     |

| Feature                | Value                                     |
|------------------------|-------------------------------------------|
|                        | Front panel mounting<br>With through-hole |
| Pneumatic connection 1 | G1/8                                      |
| Pneumatic connection 2 | G1/8                                      |
| Pneumatic connection 3 | G1/8                                      |
| Pneumatic connection 4 | G1/8                                      |
| Pneumatic connection 5 | G1/8                                      |
| Note on materials      | RoHS compliant                            |
| Cover material         | PA-reinforced                             |
| Seals material         | NBR                                       |
| Housing material       | Wrought aluminum alloy, anodized          |
| Lever material         | PA-reinforced                             |