

Round cylinder DSNU-40- -

Part number: 193993

FESTO



Data sheet

Feature	Value
Stroke	1 mm...500 mm
Piston diameter	40 mm
Cushioning	Elastic cushioning rings/pads at both ends Self-adjusting pneumatic end-position cushioning Pneumatic cushioning, adjustable at both ends
Mounting position	Any
Structural design	Piston Piston rod Cylinder barrel
Position sensing	Via proximity switch
Variants	Stroke adjustment advancing Weld spatter protection Extended external thread piston rod Internal thread on piston rod Special thread on piston rod Piston rod with external hexagon Additional slide, standard, on left Low friction for balancer applications Bearing cover without mounting thread Swiveling rod eye mounting on the end cap Metal scraper Module for reaching a specific end position in case of a pressure failure Transverse load increased High corrosion protection Reinforced piston rod Uniform, slow movement Low friction Through, hollow piston rod Additional PTFE piston guide
Protection against torsion/guide	Square piston rod
Operating pressure	0.1 MPa...1 MPa 1 bar...10 bar
Mode of operation	Double-acting
CE marking (see declaration of conformity)	as per EU explosion protection directive (ATEX)
UKCA marking (see declaration of conformity)	acc. to UK EX instructions
Explosion protection certification outside the EU	EPL Db (GB) EPL Gb (GB)
Explosion prevention and protection	Zone 1 (ATEX) Zone 1 (UKEX)

Feature	Value
	Zone 2 (ATEX) Zone 21 (ATEX) Zone 21 (UKEX) Zone 22 (ATEX)
ATEX category gas	II 2G
ATEX category for dust	II 2D
Type of ignition protection for gas	Ex h IIC T4 Gb
Type of (ignition) protection for dust	Ex h IIIC T120°C Db
Explosive ambient temperature	-20°C ≤ Ta ≤ +60°C
Operating medium	Compressed air as per ISO 8573-1:2010 [7:4:4]
Information on operating and pilot media	Operation with oil lubrication possible (required for further use)
Corrosion resistance class (CRC)	2 - Moderate corrosion stress 3 - High corrosion stress
LABS (PWIS) conformity	VDMA24364-B1/B2-L VDMA24364 Zone III
Ambient temperature	-20 °C...120 °C
Impact energy in the end positions	0.35 J...0.7 J
Cushioning length	18 mm
Theoretical force at 6 bar, retracting	633 N
Theoretical force at 6 bar, advancing	753 N
Moving mass at 0 mm stroke	230 g
Additional moving mass per 10 mm stroke	16 g
Basic weight with 0 mm stroke	661 g
Additional weight per 10 mm stroke	24 g
Type of mounting	With accessories
Pneumatic connection	G1/4
Note on materials	RoHS compliant
Cover material	Wrought aluminum alloy
Seals material	NBR TPE-U(PU)
Piston rod material	high-alloy stainless steel
Material of cylinder barrel	high-alloy stainless steel