

Flat cylinder DZF-1"- -A-P-A

Part number: 162974

FESTO



Data sheet

Feature	Value
Stroke	0.04 in...8 in
Piston diameter	1 " Equivalent diameter
Piston rod thread	3/8-24 UNF-2A
Max. angle of rotation of the piston rod +/-	1 deg
Cushioning	Elastic cushioning rings/pads at both ends
Mounting position	Any
Mode of operation	Double-acting
Structural design	Piston Piston rod
Position sensing	Via proximity switch
Variants	Piston rod at one end
Protection against torsion/guide	Oval piston
Operating pressure	0.1 MPa...1 MPa 1 bar...10 bar
Operating medium	Compressed air as per ISO 8573-1:2010 [7:4:4]
Information on operating and pilot media	Operation with oil lubrication possible (required for further use)
Corrosion resistance class (CRC)	2 - Moderate corrosion stress
LABS (PWIS) conformity	VDMA24364-B1/B2-L
Ambient temperature	-4 °F...176 °F
Impact energy in the end positions	0.074 ft-lbf
Max. torque for protection against rotation	4.42 lbf
Theoretical force at 6 bar, retracting	55.5 lbf
Theoretical force at 6 bar, advancing	66.3 lbf
Moving mass at 0 mm stroke	40 g
Moving mass with 0 inch stroke	1.41 oz
Additional moving mass per 10 mm stroke	6 g
Additional moving mass per 1 inch stroke	0.54 oz
Additional weight per 10 mm stroke	18 g
Additional weight per 1 inch stroke	1.61 oz
Basic weight with 0 mm stroke	168 g
Basic weight with 0 inch stroke	5.93 oz

Feature	Value
Type of mounting	Alternatively: With internal thread With accessories
Pneumatic connection	10-32 UNF-2B
Cover material	Die-cast aluminum Wrought aluminum alloy
Seals material	HNBR TPE-U(PU)
Housing material	Wrought aluminum alloy, anodized
Piston seal material	NBR
Piston rod material	high-alloy stainless steel