


# Clevis flange CRSNCS-40

Part number: 2895921

FESTO



## Data sheet

| Feature                                            | Value                                                                                                                                                                                                                          |
|----------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Size                                               | 40                                                                                                                                                                                                                             |
| Based on norm                                      | ISO 15552 (previously also VDMA 24562, ISO 6431, NF E49 003.1, UNI 10290)                                                                                                                                                      |
| Variants                                           | High corrosion protection                                                                                                                                                                                                      |
| Corrosion resistance class (CRC)                   | 4 - Particularly high corrosion stress                                                                                                                                                                                         |
| LABS (PWIS) conformity                             | VDMA24364-B2-L                                                                                                                                                                                                                 |
| Suitability for the production of Li-ion batteries | Metals with more than 5% by mass of copper, zinc or nickel are excluded from use. The exceptions are nickel in steel, chemically nickel-plated surfaces, printed circuit boards, cables, electrical plug connectors and coils. |
| Ambient temperature                                | -40 °C...150 °C                                                                                                                                                                                                                |
| Max. load capacity                                 | 1.5 kN                                                                                                                                                                                                                         |
| Product weight                                     | 239 g                                                                                                                                                                                                                          |
| Note on materials                                  | RoHS compliant                                                                                                                                                                                                                 |
| Mounting material                                  | high-alloy stainless steel                                                                                                                                                                                                     |
| Rod end bearing material                           | PTFE<br>High-grade steel                                                                                                                                                                                                       |
| Material of screws                                 | high-alloy stainless steel                                                                                                                                                                                                     |