

# Compact cylinder DPDM-Q-16-10-P-PA

Part number: 4834381

**FESTO**



## Data sheet

| Feature                                                   | Value                                                              |
|-----------------------------------------------------------|--------------------------------------------------------------------|
| Stroke                                                    | 10 mm                                                              |
| Piston diameter                                           | 16 mm                                                              |
| Cushioning                                                | Elastic cushioning rings/pads at both ends                         |
| Mounting position                                         | Any                                                                |
| Mode of operation                                         | Single-acting<br>Pulling                                           |
| Structural design                                         | Piston<br>Piston rod<br>Profile barrel                             |
| Position sensing                                          | Via proximity switch                                               |
| Variants                                                  | Piston rod at one end                                              |
| Protection against torsion/guide                          | Guide rod with yoke                                                |
| Operating pressure                                        | 0.2 MPa...0.8 MPa<br>2 bar...8 bar                                 |
| Operating medium                                          | Compressed air as per ISO 8573-1:2010 [7:4:4]                      |
| Information on operating and pilot media                  | Operation with oil lubrication possible (required for further use) |
| Corrosion resistance class (CRC)                          | 2 - Moderate corrosion stress                                      |
| LABS (PWIS) conformity                                    | VDMA24364-B2-L                                                     |
| Cleanroom suitability, measured according to ISO 14644-14 | Class 6 according to ISO 14644-1                                   |
| Ambient temperature                                       | -10 °C...80 °C                                                     |
| Theoretical force at 6 bar, retracting                    | 93 N                                                               |
| Theoretical force at 6 bar, advancing                     | 93 N                                                               |
| Moving mass at 0 mm stroke                                | 27 g                                                               |
| Additional moving mass per 10 mm stroke                   | 2.8 g                                                              |
| Basic weight with 0 mm stroke                             | 75 g                                                               |
| Additional weight per 10 mm stroke                        | 13.5 g                                                             |
| Type of mounting                                          | Alternatively:<br>With through-hole<br>With internal thread        |
| Pneumatic connection                                      | M5                                                                 |
| Note on materials                                         | RoHS compliant                                                     |
| Cover material                                            | Wrought aluminum alloy                                             |
| Seals material                                            | TPE-U(PU)                                                          |

| Feature             | Value                            |
|---------------------|----------------------------------|
| Housing material    | Wrought aluminum alloy, anodized |
| Piston rod material | high-alloy stainless steel       |