

# Branching module FRM-3/8-D-MIDI

Part number: 164952

**FESTO**



## Data sheet

| Feature                                                  | Value                                                       |
|----------------------------------------------------------|-------------------------------------------------------------|
| Mounting position                                        | Any                                                         |
| Structural design                                        | Branching module                                            |
| Operating pressure                                       | 0 MPa...1.6 MPa<br>0 bar...16 bar                           |
| Standard nominal flow rate in main flow direction 1 -> 2 | 6700 l/min                                                  |
| Operating medium                                         | Compressed air as per ISO 8573-1:2010 [7::-]<br>Inert gases |
| Corrosion resistance class (CRC)                         | 2 - Moderate corrosion stress                               |
| LABS (PWIS) conformity                                   | VDMA24364-B1/B2-L                                           |
| Storage temperature                                      | -10 °C...60 °C                                              |
| Air quality class at the output                          | Compressed air as per ISO 8573-1:2010 [7::-]<br>Inert gases |
| Temperature of medium                                    | -10 °C...60 °C                                              |
| Ambient temperature                                      | -10 °C...60 °C                                              |
| Product weight                                           | 522 g                                                       |
| Pneumatic connection 1                                   | G3/8                                                        |
| Pneumatic connection 2                                   | G3/8                                                        |
| Pneumatic connection 3                                   | G1/2                                                        |
| Pneumatic connection 4                                   | G1/4                                                        |
| Note on materials                                        | RoHS compliant                                              |
| Housing material                                         | Die-cast aluminum                                           |