



Quarter turn actuator DRRS-10-180-FH-PA

Part number: 8163606

FESTO



Data sheet

Feature	Value
Size	10
Cushioning angle	25.8 deg
Setting range of swivel angle for each end position	+10 / -100 deg
Axial eccentricity of plate	0.05 mm
Swivel angle	180 deg
Min. swivel angle	45 deg
Max. swivel angle	200 deg
Cushioning	Elastic cushioning rings/pads at both ends
Mounting position	Any
Structural design	Gear rack/pinion
Position sensing	Via proximity switch
Operating pressure	0.3 MPa...0.8 MPa 3 bar...8 bar
Repetition accuracy	0.05 deg
Mode of operation	Double-acting
Operating medium	Compressed air as per ISO 8573-1:2010 [7:4:4]
Information on operating and pilot media	Operation with oil lubrication possible (required for further use)
Corrosion resistance class (CRC)	1 - Low corrosion stress
LABS (PWIS) conformity	VDMA24364-C1-L
Suitability for the production of Li-ion batteries	Suitable for battery production with reduced Cu/Zn/Ni values (F1a)
Cleanroom suitability, measured according to ISO 14644-14	Class 9 according to ISO 14644-1
Storage temperature	-20 °C...60 °C
Ambient temperature	0 °C...60 °C
Theoretical torque at 6 bar	0.56 Nm
Permissible mass moment of inertia	0.0015 kgm ²
Max. bending moment	1.8 Nm
Max. axial load static	60 N
Product weight	230 g
Type of mounting	Alternatively: With mounting kit With through-hole With internal thread

Feature	Value
Pneumatic connection	M3
Note on materials	RoHS compliant
Drive shaft material	Quenched and tempered steel
Seals material	TPE-U(PU)
Housing material	Anodized aluminum
Flange shaft material	Wrought aluminum alloy
Pinion material	Quenched and tempered steel