

Fine filter MS4-LFM

Part number: 527697

FESTO



Data sheet

Feature	Value
Series	MS
Size	4
Structural design	Fiber filter
Grade of filtration	0.01 µm...1 µm
Condensate drain	Fully automatic Manual, non-detenting Manual, rotating Semiautomatic
Operating pressure	0 MPa...1.4 MPa 0 bar...14 bar 0 psi...203 psi
Operating medium	Compressed air as per ISO 8573-1:2010 [6:::4] Inert gases
Max. standard flow rate for air quality class	360 l/min
Min. standard flow rate for air quality class	54 l/min
Bowl guard	Plastic bowl guard Integrated as metal bowl
Corrosion resistance class (CRC)	2 - Moderate corrosion stress
LABS (PWIS) conformity	VDMA24364-B1/B2-L
For use in the food industry	See supplementary material information
Temperature of medium	-10 °C...60 °C
Ambient temperature	-10 °C...60 °C
Differential pressure display	Visual display With pressure sensor
Certification	c UL us - recognized (OL)
CE marking (see declaration of conformity)	as per EU explosion protection directive (ATEX)
UKCA marking (see declaration of conformity)	acc. to UK EX instructions
Explosion protection certification outside the EU	EPL Db (GB) EPL Gb (GB)
Explosion prevention and protection	Zone 1 (ATEX) Zone 1 (UKEX) Zone 2 (ATEX) Zone 21 (ATEX) Zone 21 (UKEX) Zone 22 (ATEX)

Feature	Value
ATEX category gas	II 2G
ATEX category for dust	II 2D
Type of ignition protection for gas	Ex h IIC T6 Gb X
Type of (ignition) protection for dust	Ex h IIIC T60°C Db X
Explosive ambient temperature	-10°C ≤ Ta ≤ +60°C
Type of mounting	Alternatively: In-line installation With accessories
Mounting position	Vertical ±5°
Housing material	Die-cast aluminum
Compressed air filter material	Borosilicate glass fiber
Seals material	NBR
Note on materials	RoHS compliant