


# Air solenoid valve VUVS-L25-M32C-AZD-N14-F8

Part number: 578182

**FESTO**



## Data sheet

| Feature                                           | Value                                       |
|---------------------------------------------------|---------------------------------------------|
| Valve function                                    | 3/2-way, closed, monostable                 |
| Actuation type                                    | Electrical                                  |
| Valve size                                        | 26.5 mm                                     |
| Normal nominal flow rate (normalized to DIN 1343) | 1000 l/min                                  |
| Pneumatic working port                            | 1/4 NPT                                     |
| Operating voltage                                 | Via solenoid coil, to be ordered separately |
| Operating pressure                                | -0.09 MPa...1 MPa<br>-0.9 bar...10 bar      |
| Structural design                                 | Piston gate valve                           |
| Reset method                                      | Pneumatic spring                            |
| Certification                                     | c UL us - recognized (OL)                   |
| Maritime classification                           | See certificate                             |
| Certificate issuing authority                     | DNVGL-TAA000011J                            |
| Nominal width                                     | 6.3 mm                                      |
| Exhaust air function                              | Adjustable                                  |
| Sealing principle                                 | Soft                                        |
| Mounting position                                 | Any                                         |
| Manual override                                   | Detenting<br>Non-detenting                  |
| Type of control                                   | Piloted                                     |
| Pilot air supply port                             | External                                    |
| Flow direction                                    | Reversible                                  |
| Lap                                               | Positive overlap                            |
| Pilot pressure MPa                                | 0.25 MPa...1 MPa                            |
| Pilot pressure                                    | 2.5 bar...10 bar                            |
| b-value                                           | 0.3                                         |
| C value                                           | 4.7 l/sbar                                  |
| Switching time off                                | 26 ms                                       |
| On switching time                                 | 13 ms                                       |
| Max. positive test pulse with 0 signal            | 2000 µs                                     |
| Max. negative test pulse on 1 signal              | 3600 µs                                     |
| Coil characteristics                              | See solenoid coil, to be ordered separately |

| Feature                                                   | Value                                                                                |
|-----------------------------------------------------------|--------------------------------------------------------------------------------------|
| Operating medium                                          | Compressed air as per ISO 8573-1:2010 [7:4:4]                                        |
| Information on operating and pilot media                  | Operation with oil lubrication possible (required for further use)                   |
| Vibration resistance                                      | Transport application test with severity level 2 as per FN 942017-4 and EN 60068-2-6 |
| Shock resistance                                          | Shock test with severity level 2 as per FN 942017-5 and EN 60068-2-27                |
| Corrosion resistance class (CRC)                          | 2 - Moderate corrosion stress                                                        |
| LABS (PWIS) conformity                                    | VDMA24364-B1/B2-L                                                                    |
| Cleanroom suitability, measured according to ISO 14644-14 | Class 6 according to ISO 14644-1                                                     |
| Temperature of medium                                     | -10 °C...60 °C                                                                       |
| Pilot medium                                              | Compressed air as per ISO 8573-1:2010 [7:4:4]                                        |
| Ambient temperature                                       | -10 °C...60 °C                                                                       |
| Product weight                                            | 244 g                                                                                |
| Type of mounting                                          | Alternatively:<br>On terminal strip<br>With through-hole                             |
| Venting hole connection                                   | Not ducted                                                                           |
| Pilot exhaust air port 82                                 | 10-32 UNF-2B                                                                         |
| Pneumatic connection 1                                    | 1/4 NPT                                                                              |
| Pneumatic connection 2                                    | 1/4 NPT                                                                              |
| Pneumatic connection 3                                    | 1/4 NPT                                                                              |
| Note on materials                                         | RoHS compliant                                                                       |
| Seals material                                            | HNBR<br>NBR                                                                          |
| Housing material                                          | Die-cast aluminum<br>Painted                                                         |
| Piston slide material                                     | Wrought aluminum alloy                                                               |
| Material of screws                                        | Galvanized steel                                                                     |