


**Ball valve**  
**VZBM-11/2-RP-25-F-3T-F0405-B2B3**  
 Part number: 4451859

**FESTO**



**Data sheet**

| Feature                                                                 | Value                                                                                                  |
|-------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------|
| Structural design                                                       | 3-way ball valve<br>T hole                                                                             |
| Actuation type                                                          | Mechanical                                                                                             |
| Sealing principle                                                       | Soft                                                                                                   |
| Mounting position                                                       | Any                                                                                                    |
| Type of mounting                                                        | In-line installation                                                                                   |
| Fitting connection                                                      | Rp1 1/2                                                                                                |
| Switching position indication                                           | Slot direction = flow direction                                                                        |
| Flange hole pattern                                                     | F04<br>F05                                                                                             |
| Inside diameter                                                         | 38 mm                                                                                                  |
| Nominal width DN                                                        | 40                                                                                                     |
| Valve function                                                          | 3/2                                                                                                    |
| Flow direction                                                          | Reversible                                                                                             |
| Nominal pressure of fitting PN                                          | 25                                                                                                     |
| Breakaway torque at differential pressure, nominal pressure, fitting PN | 26.7 Nm                                                                                                |
| Based on norm                                                           | EN 10226-1<br>ISO 5211                                                                                 |
| Medium                                                                  | Compressed air as per ISO 8573-1:2010 [-:~:]<br>Inert gas<br>Water – no water vapor<br>Neutral liquids |
| Temperature of medium                                                   | -20 °C...130 °C                                                                                        |
| Flow rate Kv type T corner                                              | 200 m³/h                                                                                               |
| Note on materials                                                       | RoHS compliant                                                                                         |
| LABS (PWIS) conformity                                                  | VDMA24364 Zone III                                                                                     |
| Housing material                                                        | Brass<br>Nickel-plated                                                                                 |

| Feature                                    | Value                                  |
|--------------------------------------------|----------------------------------------|
| Material number of housing                 | CW617N                                 |
| Seals material                             | HNBR<br>PTFE                           |
| Ball material                              | Brass<br>Chrome-plated                 |
| Material number for ball                   | CW614N                                 |
| Shaft material                             | Brass                                  |
| Material number for shaft                  | CW614N                                 |
| Product weight                             | 3190 g                                 |
| CE marking (see declaration of conformity) | as per EU pressure equipment directive |
| Corrosion resistance class (CRC)           | 1 - Low corrosion stress               |