


**Filter**  
**MS6-LF-AGE-E-R-V**  
 Part number: 8232878

**FESTO**



## Data sheet

| Feature                                           | Value                                                        |
|---------------------------------------------------|--------------------------------------------------------------|
| Size                                              | 6                                                            |
| Series                                            | MS                                                           |
| Mounting position                                 | Vertical $\pm 5^\circ$                                       |
| Grade of filtration                               | 40 $\mu\text{m}$                                             |
| Condensate drain                                  | Fully automatic                                              |
| Structural design                                 | Sinter filter with centrifugal separator                     |
| Bowl guard                                        | Plastic bowl guard                                           |
| Degree of condensate separation                   | 75 %                                                         |
| Operating pressure                                | 0.2 MPa...1.2 MPa<br>2 bar...12 bar<br>29 psi...174 psi      |
| Normal nominal flow rate (normalized to DIN 1343) | 4100 l/min                                                   |
| Operating medium                                  | Compressed air as per ISO 8573-1:2010 [7:9:-]<br>Inert gases |
| Corrosion resistance class (CRC)                  | 2 - Moderate corrosion stress                                |
| LABS (PWIS) conformity                            | VDMA24364-B1/B2-L                                            |
| Storage temperature                               | -10 °C...60 °C                                               |
| For use in the food industry                      | See supplementary material information                       |
| Air quality class at the output                   | Compressed air as per ISO 8573-1:2010 [7:8:4]                |
| Temperature of medium                             | -10 °C...60 °C                                               |
| Ambient temperature                               | -10 °C...60 °C                                               |
| Pore size                                         | 40 $\mu\text{m}$                                             |
| Product weight                                    | 900 g                                                        |
| Type of mounting                                  | Alternatively:<br>In-line installation<br>With accessories   |
| Pneumatic connection 1                            | G3/4                                                         |
| Pneumatic connection 2                            | G3/4                                                         |
| Note on materials                                 | RoHS compliant                                               |
| Material of sub-base                              | Die-cast aluminum                                            |
| Seals material                                    | NBR                                                          |
| Compressed air filter material                    | Protective grounding                                         |

| Feature                  | Value             |
|--------------------------|-------------------|
| Housing material         | Die-cast aluminum |
| Material of bowl         | PC                |
| Separating disc material | POM               |