


Distributor
NEDY-L2R1-V1-C1W4L-U-0.3L-M12G4-2.5R
Part number: 8035783

FESTO



Data sheet

Feature	Value
Based on norm	EN 175301-803 EN 61076-2-101
Structural design	Y-distributor with cables at both ends
Distributor type	2 to 1
Signal status display	Yellow LED
Cable designation	With label holder
Type of mounting	With through-hole for M2 screw With accessories
Product weight	104 g
Electrical connection 1, function	Control side
Electrical connection 1, design	Round
Electrical connection 1, connection type	Plug
Electrical connection 1, cable outlet	Straight
Electrical connection 1, connection technology	M12x1 A-coded as per EN 61076-2-101
Electrical connection 1, number of pins/wires	4
Electrical connection 1, occupied pins/wires	3
Electrical connection 1, type of mounting	Screw-type lock with hexagon AF13 and vertical knurling Rotatable Compatible with rotatable/non-rotatable screw-type lock
Electrical connection 2, function	Field device side
Electrical connection 2, design	Square
Electrical connection 2, connection type	2x port
Electrical connection 2, cable outlet	Angled
Electrical connection 2, connection technology	Connection diagram type C as per EN 175301-803
Electrical connection 2, number of pins/wires	4
Electrical connection 2, occupied pins/wires	2
Electrical connection 2, type of mounting	on solenoid valve with M2.5 central screw
DC operating voltage range	20.4 V...27.6 V
Current rating at 40° C	4 A

Feature	Value
Surge resistance	0.8 kV
Cable length 1	2.5 m
Cable length 2	0.3 m
Cable characteristic	suitable for energy chains/robot applications
Connector cable test conditions	Flexural strength: as per Festo standard Test conditions on request Torsion resistance: > 300,000 cycles, $\pm 270^\circ/0.1$ m Energy chain: > 5 million cycles, bending radius 28 mm
Bending radius 1, flexible cable installation	39 mm
Bending radius 2, flexible cable installation	39 mm
Cable diameter 1	3.8 mm
Cable diameter 2	3.8 mm
Nominal conductor cross section	0.25 mm ²
Degree of protection	IP65 IP67
Ambient temperature	-20 °C...80 °C
Note on ambient temperature	-10 - 40 °C when mounted via through-hole
Ambient temperature with flexible cable installation	-20 °C...80 °C
Storage temperature	-20 °C...80 °C
CE marking (see declaration of conformity)	As per EU RoHS directive
UKCA marking (see declaration of conformity)	To UK RoHS instructions
LABS (PWIS) conformity	VDMA24364-B2-L
Note on materials	RoHS compliant Halogen-free Contains no phosphoric acid esters
Contamination level	3
Corrosion resistance class (CRC)	1 - Low corrosion stress
Material of cable sheath	TPE-U(PUR)
Color cable sheath	Gray
Housing material	PA PC TPE-U(PUR)
Housing colour	Black
Seals material	NBR
Material of pin contacts	Gold-plated copper alloy Silver-plated copper alloy
Threaded sleeve material	Die-cast zinc