

# ISO cylinder DSNU-25-60-PPV-A

Part number: 1908317

**FESTO**



## Data sheet

| Feature                                                   | Value                                                              |
|-----------------------------------------------------------|--------------------------------------------------------------------|
| Stroke                                                    | 60 mm                                                              |
| Piston diameter                                           | 25 mm                                                              |
| Piston rod thread                                         | M10x1.25                                                           |
| Cushioning                                                | Pneumatic cushioning, adjustable at both ends                      |
| Mounting position                                         | Any                                                                |
| Conforms to standard                                      | CETOP RP 52 P<br>ISO 6432                                          |
| Piston rod end                                            | External thread                                                    |
| Structural design                                         | Piston<br>Piston rod<br>Cylinder barrel                            |
| Position sensing                                          | Via proximity switch                                               |
| Variants                                                  | Piston rod at one end                                              |
| Operating pressure                                        | 0.1 MPa...1 MPa<br>1 bar...10 bar                                  |
| Mode of operation                                         | Double-acting                                                      |
| Operating medium                                          | Compressed air as per ISO 8573-1:2010 [7:4:4]                      |
| Information on operating and pilot media                  | Operation with oil lubrication possible (required for further use) |
| Corrosion resistance class (CRC)                          | 2 - Moderate corrosion stress                                      |
| LABS (PWIS) conformity                                    | VDMA24364-B1/B2-L                                                  |
| Cleanroom suitability, measured according to ISO 14644-14 | Class 6 according to ISO 14644-1                                   |
| Ambient temperature                                       | -20 °C...80 °C                                                     |
| Impact energy in the end positions                        | 0.3 J                                                              |
| Cushioning length                                         | 17 mm                                                              |
| Theoretical force at 6 bar, retracting                    | 247.4 N                                                            |
| Theoretical force at 6 bar, advancing                     | 294.5 N                                                            |
| Moving mass at 0 mm stroke                                | 71 g                                                               |
| Additional moving mass per 10 mm stroke                   | 6 g                                                                |
| Basic weight with 0 mm stroke                             | 238 g                                                              |
| Additional weight per 10 mm stroke                        | 11 g                                                               |
| Type of mounting                                          | With accessories                                                   |
| Pneumatic connection                                      | G1/8                                                               |

| Feature                     | Value                                        |
|-----------------------------|----------------------------------------------|
| Note on materials           | RoHS compliant                               |
| Cover material              | Wrought aluminum alloy<br>Colorless anodized |
| Seals material              | NBR<br>TPE-U(PU)                             |
| Piston rod material         | high-alloy stainless steel                   |
| Material of cylinder barrel | high-alloy stainless steel                   |