


Controller CPX-E-CEC-M1-PN

Part number: 4252743

FESTO



Data sheet

Feature	Value
Width dimension	18.9 mm
Type of mounting	With DIN rail
Product weight	288 g
Mounting position	Vertical Horizontal
Ambient temperature	-5 °C...50 °C
Note on ambient temperature	-5 - 60 °C for vertical installation
Storage temperature	-20 °C...70 °C
Relative air humidity	95% Non-condensating
Degree of protection	IP20
Corrosion resistance class (CRC)	0 - No corrosion stress
Protection against direct and indirect contact	PELV
LABS (PWIS) conformity	VDMA24364 Zone III
CE marking (see declaration of conformity)	As per EU EMC directive As per EU RoHS directive
Certification	RCM compliance mark c UL us - Listed (OL)
Note on materials	RoHS compliant
Diagnostics via LED	Force mode Module status Network error Network status, engineering port 1 Engineering port 2 network status EtherCAT network status Network status, port 1 Network status, port 2 Run Power supply for electronics/sensors Load power supply System fault Maintenance required
Control elements	DIP switch for RUN/STOP Optional: Operator unit CDSB
Fieldbus interface, protocol	LLDP MRP, MRPD (ring redundancy) PROFINET I&M0 .. 3

Feature	Value
	PROFINET IO PROFINET RT PROFINET shared device SNMP
Fieldbus interface, connection type	2x port
Fieldbus interface, connection technology	RJ45
Fieldbus interface, number of poles/wires	8
Fieldbus interface 2, type	Ethernet
Fieldbus interface 2, protocol	CoE EoE EtherCAT EtherCAT® Master FoE
Fieldbus interface 2, function	Forwarding bus connection
Fieldbus interface 2, connection type	Socket
Fieldbus interface 2, connection technology	RJ45
Fieldbus interface 2, number of poles/wires	8
Fieldbus interface 2, galvanic isolation	Yes
Fieldbus interface 2, transmission rate	100 Mbit/s
Ethernet interface, connection type	2x port
Ethernet interface, protocol	EasyIP Modbus® TCP OPC-UA TCP/IP
Ethernet interface, function	Diagnostics Switch
Ethernet interface, connection technology	RJ45
Ethernet interface, number of poles/wires	8
Ethernet interface, transmission rate	10 Mbit/s 100 Mbit/s
Max. address capacity inputs	64 byte
Fieldbus interface, max. address volume for inputs	512 byte
Max. address capacity outputs	64 byte
Fieldbus interface, max. address volume for outputs	512 byte
System parameter	Diagnostic memory Fail-safe response System startup
Module parameters	Channel alarm bundling Undervoltage diagnostics Channel alarms for undervoltage Analog module process value representation
Configuration support	Operator unit CDSB CODESYS V3 GSDML file
Additional functions	CODESYS V3 with SoftMotion
Power supply, function	Electronics and sensors
Power supply, type of connection	Terminal strip
Power supply, note on connection type	> 4 A and UL 2x terminal strip for power supply
Power supply, connection technology	Spring-loaded terminal
Power supply, number of pins/wires	4
Nominal operating voltage DC for electronics/sensors	24 V
Permissible voltage fluctuations for electronics/sensors	±25%
Power supply, conductor diameter	0.2 mm²...1.5 mm²
Power supply, information on conductor diameter	0.2 - 2.5 mm² for flexible conductors without cable end sleeves
Intrinsic current consumption at nominal operating voltage for electronics/sensors	Typically 150 mA
Power failure buffering	20 ms
Reverse polarity protection	24 V sensor supply against 0 V sensor supply

Feature	Value
Program memory	100 MB user program