


## Sub-base VMPAL-AP-10-RV

Part number: 8035230

**FESTO**



## Data sheet

| Feature                                  | Value                                                              |
|------------------------------------------|--------------------------------------------------------------------|
| Width                                    | 10 mm<br>10.7 mm                                                   |
| Length                                   | 107.3 mm                                                           |
| Width dimension                          | 10.7 mm                                                            |
| Max. no. of valve positions              | 1                                                                  |
| Integrated function                      | Check valve                                                        |
| Flow direction                           | Non-reversible                                                     |
| Valve manifold design                    | Interchangeable valve sizes                                        |
| Operating pressure                       | -0.09 MPa...1 MPa<br>-0.9 bar...10 bar                             |
| Pilot pressure MPa                       | 0.3 MPa...0.8 MPa                                                  |
| Pilot pressure                           | 3 bar...8 bar                                                      |
| Suitability for vacuum                   | No                                                                 |
| Operating medium                         | Compressed air as per ISO 8573-1:2010 [7:4:4]                      |
| Information on operating and pilot media | Operation with oil lubrication possible (required for further use) |
| Corrosion resistance class (CRC)         | 3 - High corrosion stress                                          |
| LABS (PWIS) conformity                   | VDMA24364-B1/B2-L                                                  |
| Ambient temperature                      | -5 °C...50 °C                                                      |
| Product weight                           | 25 g                                                               |
| Pneumatic connection 2                   | for 10 mm cartridge                                                |
| Pneumatic connection 4                   | for 10 mm cartridge                                                |
| Note on materials                        | RoHS compliant                                                     |
| Material of sub-base                     | PA-reinforced                                                      |