

Pneumatic interface VABA-S6-1-X5

Part number: 8154036

FESTO



Data sheet

Feature	Value
Vibration resistance	Transport application test with severity level 2 as per FN 942017-4 and EN 60068-2-6
Note on vibration resistance	SG2 on wall mounting
Shock resistance	Shock test with severity level 2 as per FN 942017-5 and EN 60068-2-27
Note on shock resistance	SG2 on wall mounting
Valve manifold interface	Type 44, VTSA Type 45, VTSA-F
Reverse polarity protection	Yes
Diagnostics via LED	Diagnostics per module Load power supply
Diagnose per internal communication	Load switch-off Communication error Short-circuit/overload in output signal Electronics/sensors overvoltage Overvoltage load Electronics/sensors undervoltage Undervoltage load
Max. no. of valve positions	16 for double-solenoid valves 32 for single-solenoid valves
Max. no. of solenoid coils	32
Module code (hex/dec)	0x3044/12356d
Module parameters	Activation of diagnosis in case of overload/short circuit Condition counter limit/actual value Configuration of voltage monitoring, load supply PL Response in error state
Internal cycle time	< 1 ms
Dimensions W x L x H	70.5 mm x 142 mm x 102.6 mm
Fuse protection (short circuit)	Internal electronic fuse per pneumatic valve output
Intrinsic current consumption at nominal operating voltage for electronics/sensors	typically 27 mA
Intrinsic current consumption at nominal operating voltage load	typically 17 mA
Note regarding operating voltage	SELV/PELV fixed power supplies required Note voltage drop
Nominal operating voltage DC for electronics/sensors	24 V
Nominal operating voltage DC load	24 V
Power failure buffering	10 ms

Feature	Value
Potential separation between the supply voltages electronics/sensor technology and load/valves	Yes
Contamination level	2
Permissible voltage fluctuations for electronics/sensors	±25%
Permissible voltage fluctuations load	±10%
Undervoltage load/valves (diagnostic message)	21.6 V
Corrosion resistance class (CRC)	0 - No corrosion stress
LABS (PWIS) conformity	VDMA24364-B2-L
Storage temperature	-20 °C...70 °C
Relative air humidity	5 - 95% Non-condensating
Protection class	III
Overvoltage category	II
Ambient temperature	-20 °C...50 °C
Note on ambient temperature	Observe ambient temperature derating according to IEC 61131-2:2017
Nominal altitude of use above sea level	<= 2000 m ASL (> 79.5 kPa)
Max. installation height	3500 m
Information on max. installation height	> 2000 m ASL (< 79.5 kPa) Observe ambient temperature derating according to IEC 61131-2:2017
Product weight	1245 g
Electrical actuation	Fieldbus
Communication interface, protocol	AP
Type of mounting	with through-hole for M6 screw
Note on materials	RoHS compliant Halogen-free Contains no phosphoric acid esters
Cover material	Zinc die-cast metal, powder-coated
Seals material	NBR PUR
Housing material	Aluminum
Material of screws	Steel, nickel-plated