


# Twin cylinder DPZJ-25-50-P-A-KF-S2

Part number: 162120

FESTO



## Data sheet

| Feature                                  | Value                                                              |
|------------------------------------------|--------------------------------------------------------------------|
| Stroke                                   | 50 mm                                                              |
| Adjustable end position range/length     | 10 mm                                                              |
| Piston diameter                          | 25 mm                                                              |
| Drive unit operating mode                | Yoke                                                               |
| Cushioning                               | Elastic cushioning rings/pads at both ends                         |
| Mounting position                        | Any                                                                |
| Guide                                    | Recirculating ball bearing                                         |
| Structural design                        | Guide                                                              |
| Position sensing                         | Via proximity switch                                               |
| Variants                                 | Through piston rod                                                 |
| Operating pressure                       | 0.1 MPa...1 MPa<br>1 bar...10 bar                                  |
| Max. speed                               | 1 m/s                                                              |
| Mode of operation                        | Double-acting                                                      |
| Operating medium                         | Compressed air as per ISO 8573-1:2010 [7:4:4]                      |
| Information on operating and pilot media | Operation with oil lubrication possible (required for further use) |
| Corrosion resistance class (CRC)         | 0 - No corrosion stress                                            |
| LABS (PWIS) conformity                   | VDMA24364-B1/B2-L                                                  |
| Ambient temperature                      | -20 °C...80 °C                                                     |
| Impact energy in the end positions       | 0.3 Nm                                                             |
| Theoretical force at 6 bar, retracting   | 452 N                                                              |
| Theoretical force at 6 bar, advancing    | 452 N                                                              |
| Alternative connections                  | See product drawing                                                |
| Pneumatic connection                     | M5                                                                 |
| Cover material                           | Wrought aluminum alloy                                             |
| Seals material                           | NBR                                                                |
| Housing material                         | Wrought aluminum alloy                                             |
| Piston rod material                      | Case-hardened steel                                                |