


# Cable

## NEYM-F- -Q9

Part number: 8242219

FESTO



## Data sheet

| Feature                                              | Value                                                                                                         |
|------------------------------------------------------|---------------------------------------------------------------------------------------------------------------|
| Product weight                                       | 0.223 kg...6.69 kg                                                                                            |
| DC operating voltage range                           | 0 V...850 V                                                                                                   |
| Operating voltage range AC                           | 0 V...630 V                                                                                                   |
| Current rating                                       | 17.8 A                                                                                                        |
| Protective earth connection                          | Not available                                                                                                 |
| Cable diameter                                       | 11.5 mm                                                                                                       |
| Cable design                                         | 4 x 1.5 mm <sup>2</sup> + (2 x 0.75 mm <sup>2</sup> ) + (4 x 0.14 mm <sup>2</sup> + 2 x 0.2 mm <sup>2</sup> ) |
| Degree of protection                                 | IP00                                                                                                          |
| Ambient temperature                                  | 90 °C                                                                                                         |
| Ambient temperature with flexible cable installation | 90 °C                                                                                                         |
| Storage temperature                                  | 70 °C                                                                                                         |
| LABS (PWIS) conformity                               | VDMA24364-B2-L                                                                                                |
| Note on materials                                    | RoHS compliant                                                                                                |
| Material of cable sheath                             | TPE-E                                                                                                         |
| Color cable sheath                                   | Gray                                                                                                          |