


Manifold sub-base VABX-A-S-EL-E12-CTED-MPRJ45-SHUH-XL

Part number: 8208384

FESTO



Data sheet

Feature	Value
Size	1 2
Vibration resistance	Transport application test with severity level 2 as per FN 942017-4 and EN 60068-2-6
Shock resistance	Shock test with severity level 2 as per FN 942017-5 and EN 60068-2-27
Connection position	Lateral
Reverse polarity protection	Yes
Diagnostics via LED	Diagnostics per module
Diagnose per internal communication	Logic supply undervoltage PS Logic supply overvoltage PS
Valve manifold design	Interchangeable valve sizes
Max. no. of solenoid coils	128
Compatible with	Valve manifold VTUX-A-S
Dimensions W x L x H	26 mm x 104 mm x 92 mm
Inductive protective circuit	Installed
Intrinsic current consumption at nominal operating voltage for electronics/sensors	Typically 50 mA
Note regarding operating voltage	SELV/PELV fixed power supplies required Note voltage drop
Power consumption at 24 VDC	1.2 W
Max. power supply	2 x 4 A (external fuse required)
Nominal operating voltage DC for electronics/sensors	24 V
Nominal operating voltage DC load	24 V
Power failure buffering	10 ms
Electrical isolation of outputs between channel - internal communication	Yes
Potential separation between the supply voltages electronics/sensor technology and load/valves	Yes
Protocol	CC-Link IE Field Basic EtherCAT EtherNet/IP Modbus® TCP PROFINET
Contamination level	2
Permissible voltage fluctuations for electronics/sensors	±25%

Feature	Value
Permissible voltage fluctuations load	±10%
Power supply, function	Incoming electronics/sensors and load
Power supply, type of connection	Plug
Power supply, connection technology	Pin header, 5-pin
Power supply, number of pins/wires	5
Undervoltage load/valves (diagnostic message)	21.1 V
Certification	RCM compliance mark
KC characters	KC-EMV
CE marking (see declaration of conformity)	As per EU EMC directive As per EU RoHS directive
UKCA marking (see declaration of conformity)	To UK instructions for EMC To UK RoHS instructions
Corrosion resistance class (CRC)	2 - Moderate corrosion stress
LABS (PWIS) conformity	VDMA24364-B1/B2-L
Storage temperature	-20 °C...70 °C
Relative air humidity	5 - 95%
Protection against direct and indirect contact	PELV SELV
Degree of protection	IP20
Overvoltage category	II
Ambient temperature	-5 °C...50 °C
Nominal altitude of use above sea level	≤ 2000 m NHN
Max. installation height	3500 m
Max. tightening torque for wall mounting	6 Nm
Product weight	227 g
Electrical actuation	AP interface
Max. cable length	100 m
Communication interface, function	System communication XF1 IN / XF2 OUT
Communication interface, connection type	2x port
Communication interface, connection technology	RJ45
Communication interface, number of pins/wires	4
Communication interface, protocol	CC-Link IE Field Basic EtherCAT EtherNet/IP Modbus® TCP PROFINET
Communication interface, shielding	Yes
Cable outlet	Straight
Sub-base mounting type	With through-hole
Type of mounting	with through-hole for M5 screw
Pneumatic connection 1	for 15 mm cartridge
Pneumatic connection 5	for 15 mm cartridge
Note on materials	RoHS compliant
Material of sub-base	PA-reinforced
Cover material	PA-reinforced
Seals material	NBR
Sleeve material	high-alloy stainless steel
Clip material	high-alloy stainless steel
Nut material	high-alloy stainless steel