

# Pneumatic muffler AMTE-M-LH-G12

Part number: 1205863

**FESTO**



## Data sheet

| Feature                                  | Value                                                              |
|------------------------------------------|--------------------------------------------------------------------|
| Mounting position                        | Any                                                                |
| Pack size                                | 10                                                                 |
| Operating pressure                       | 0 MPa...1 MPa<br>0 bar...10 bar                                    |
| Flow rate with respect to atmosphere     | 10500 l/min                                                        |
| Explosion prevention and protection      | Zone 1 (ATEX)<br>Zone 2 (ATEX)<br>Zone 21 (ATEX)<br>Zone 22 (ATEX) |
| Operating medium                         | Compressed air as per ISO 8573-1:2010 [7:::]                       |
| Information on operating and pilot media | Lubricated operation possible                                      |
| Corrosion resistance class (CRC)         | 1 - Low corrosion stress                                           |
| LABS (PWIS) conformity                   | VDMA24364-B1/B2-L                                                  |
| Noise level                              | 88 dB(A)                                                           |
| Ambient temperature                      | -40 °C...80 °C                                                     |
| Product weight                           | 43 g                                                               |
| Pneumatic connection                     | G1/2                                                               |
| Cushioning insert material               | Bronze                                                             |
| Material of screwed plug                 | Brass                                                              |
| Note on materials                        | RoHS compliant                                                     |