


# On/off valve HEE-1/2-D-MIDI-24

Part number: 172944

FESTO



## Data sheet

| Feature                                           | Value                                                              |
|---------------------------------------------------|--------------------------------------------------------------------|
| Structural design                                 | Piston gate valve                                                  |
| Actuation type                                    | Electrical                                                         |
| Sealing principle                                 | Soft                                                               |
| Exhaust air function                              | Cannot be throttled                                                |
| Manual override                                   | Detenting                                                          |
| Reset method                                      | Mechanical spring                                                  |
| Type of control                                   | Piloted                                                            |
| Valve function                                    | 3/2-way, closed, monostable                                        |
| Operating pressure                                | 0.25 MPa...1.6 MPa<br>2.5 bar...16 bar                             |
| Lap                                               | Positive overlap                                                   |
| C value                                           | 17 l/sbar                                                          |
| b-value                                           | 0.3                                                                |
| Normal nominal flow rate (normalized to DIN 1343) | 3600 l/min                                                         |
| Duty cycle                                        | 100%                                                               |
| Coil characteristics                              | 24 V DC: 2.5 W                                                     |
| Permissible voltage fluctuations                  | +/- 10%                                                            |
| Operating medium                                  | Compressed air as per ISO 8573-1:2010 [7:4:4]<br>Inert gases       |
| Information on operating and pilot media          | Operation with oil lubrication possible (required for further use) |
| Corrosion resistance class (CRC)                  | 2 - Moderate corrosion stress                                      |
| Note on materials                                 | RoHS compliant                                                     |
| LABS (PWIS) conformity                            | VDMA24364-B1/B2-L                                                  |
| Temperature of medium                             | -10 °C...60 °C                                                     |
| Ambient temperature                               | -10 °C...60 °C                                                     |
| Type of mounting                                  | In-line installation<br>With accessories                           |
| Mounting position                                 | Any                                                                |
| Flow direction                                    | Non-reversible                                                     |
| Product weight                                    | 500 g                                                              |
| Pneumatic connection 1                            | G1/2                                                               |
| Pneumatic connection 2                            | G1/2                                                               |

| Feature                         | Value                                                        |
|---------------------------------|--------------------------------------------------------------|
| Pneumatic connection 3          | G1/4                                                         |
| Air quality class at the output | Compressed air as per ISO 8573-1:2010 [7:4:4]<br>Inert gases |
| Electrical connection           | Type C<br>Plug<br>As per DIN EN 175301-803                   |
| Signal status display           | With accessories                                             |
| Seals material                  | NBR                                                          |
| Housing material                | Die-cast aluminum                                            |