

Mini slide DGST-25- -

Part number: 8073897

FESTO



Data sheet

Feature	Value
Stroke	10 mm...200 mm
Adjustable end-position range/front length	5.95 mm...47 mm
Adjustable end-position range/rear length	6.3 mm...45.4 mm
Piston diameter	25 mm
Drive unit operating mode	Yoke
Cushioning	Short elastic cushioning rings/pads at both ends Elastomer cushioning, at both ends, stroke not adjustable Elastic cushioning rings/pads at both ends Elastic cushioning rings/pads at both ends with fixed stop External hydraulic cushioning
Mounting position	Any
Guide	Ball bearing cage guide
Structural design	Double piston Yoke Piston rod Slide
Position sensing	Via proximity switch
Variants	Metals with copper, zinc or nickel by mass as main constituent are excluded from use. Exceptions are nickel in steel, chemically nickel-plated surfaces, printed circuit boards, cables, electrical plug connectors and coils.
Operating pressure	0.1 MPa...0.8 MPa 1 bar...8 bar 14.5 psi...116 psi
Max. speed	0.5 m/s...0.8 m/s
Repetition accuracy	<= 0.3 mm <= 0.02 mm
Mode of operation	Double-acting
Operating medium	Compressed air as per ISO 8573-1:2010 [7:4:4]
Information on operating and pilot media	Operation with oil lubrication possible (required for further use)
Corrosion resistance class (CRC)	1 - Low corrosion stress
LABS (PWIS) conformity	VDMA24364-B1/B2-L
Suitability for the production of Li-ion batteries	Suitable for battery production with reduced Cu/Zn/Ni values (F1a)
Cleanroom suitability, measured according to ISO 14644-14	Class 6 according to ISO 14644-1
Ambient temperature	-10 °C...60 °C

Feature	Value
Impact energy in the end positions	0.3 J...6 J
Cushioning length	1.2 mm...10 mm
Max. force F _y	1030 N...1840 N
Max. force F _z	1030 N...1840 N
Max. torque M _x	12 Nm...20 Nm
Max. torque M _y	11 Nm...21 Nm
Max. torque M _z	11 Nm...21 Nm
Theoretical force at 6 bar, retracting	495 N
Theoretical force at 6 bar, advancing	589 N
Moving mass	714 g...2418.5 g
Product weight	1463 g...5076 g
Type of mounting	With through-hole
Pneumatic connection	G1/8
Note on materials	RoHS compliant
Cover material	Wrought aluminum alloy
Seals material	HNBR
Guide material	POM TPE-E High-alloy steel
Housing material	Wrought aluminum alloy
Piston rod material	high-alloy stainless steel