

# Flange mounting CRFNG-63

Part number: 161849

FESTO



## Data sheet

| Feature                                            | Value                                                                                                                                                                                                                          |
|----------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Size                                               | 63                                                                                                                                                                                                                             |
| Mounting position                                  | Any                                                                                                                                                                                                                            |
| Conforms to standard                               | ISO 15552 (previously also VDMA 24562, ISO 6431, NF E49 003.1, UNI 10290)                                                                                                                                                      |
| Corrosion resistance class (CRC)                   | 4 - Particularly high corrosion stress                                                                                                                                                                                         |
| LABS (PWIS) conformity                             | VDMA24364-B2-L                                                                                                                                                                                                                 |
| Suitability for the production of Li-ion batteries | Metals with more than 5% by mass of copper, zinc or nickel are excluded from use. The exceptions are nickel in steel, chemically nickel-plated surfaces, printed circuit boards, cables, electrical plug connectors and coils. |
| Ambient temperature                                | -40 °C...150 °C                                                                                                                                                                                                                |
| Product weight                                     | 680 g                                                                                                                                                                                                                          |
| Mounting material                                  | high-alloy stainless steel                                                                                                                                                                                                     |
| Material of screws                                 | high-alloy stainless steel                                                                                                                                                                                                     |