

# Solenoid coil MSW-230AC-60-OD

Part number: 34408

**FESTO**



## Data sheet

| Feature                                      | Value                                                     |
|----------------------------------------------|-----------------------------------------------------------|
| Actuation type                               | Electrical                                                |
| Mounting position                            | Any                                                       |
| Min. pick-up time                            | 10 ms                                                     |
| Duty cycle                                   | 100%                                                      |
| Insulation class                             | F                                                         |
| Coil characteristics                         | 220 V AC: 60 Hz, pick-up power 36 VA, holding power 28 VA |
| Permissible voltage fluctuations             | +/- 10%                                                   |
| CE marking (see declaration of conformity)   | As per EU low voltage directive                           |
| UKCA marking (see declaration of conformity) | To UK instructions for electrical equipment               |
| LABS (PWIS) conformity                       | VDMA24364-C1-L                                            |
| Storage temperature                          | -10 °C...60 °C                                            |
| Degree of protection                         | IP65                                                      |
| Ambient temperature                          | -5 °C...50 °C                                             |
| Product weight                               | 150 g                                                     |
| Electrical connection                        | Type A<br>Plug<br>As per EN 175301-803                    |
| Type of mounting                             | External hexagon 1/8<br>Retaining clip                    |
| Note on materials                            | RoHS compliant                                            |
| Solenoid coil material                       | Duroplast                                                 |
| Material of pin contacts                     | Tin-plated brass                                          |
| Material of winding                          | Copper                                                    |