

# Connecting cable NEBV-S1G25-K-2.5-N-LE15

Part number: 538222

**FESTO**



## Data sheet

| Feature                                              | Value                            |
|------------------------------------------------------|----------------------------------|
| Type of mounting                                     | 4-40 UNC-2B                      |
| Product weight                                       | 370 g                            |
| Electrical connection 1                              | Socket Sub-D, 25-pin             |
| Electrical connection 2                              | Open end, 15-core                |
| Nominal operating voltage DC                         | 24 V                             |
| Cable length                                         | 2.5 m                            |
| Cable characteristic                                 | Standard                         |
| Min. cable bending radius                            | 90 mm                            |
| Cable diameter                                       | 9 mm                             |
| Cable design                                         | 15 x 0.34 mm <sup>2</sup>        |
| Degree of protection                                 | IP65<br>IP67<br>In mounted state |
| Ambient temperature with flexible cable installation | -5 °C...50 °C                    |
| CE marking (see declaration of conformity)           | As per EU RoHS directive         |
| UKCA marking (see declaration of conformity)         | To UK RoHS instructions          |
| LABS (PWIS) conformity                               | VDMA24364-B2-L                   |
| Note on materials                                    | RoHS compliant                   |
| Corrosion resistance class (CRC)                     | 2 - Moderate corrosion stress    |
| Material of cable sheath                             | PVC                              |
| Housing material                                     | PBT                              |
| Material of union nut                                | PA                               |
| Seals material                                       | TPE-O                            |