

Push-in fitting QS-G3/4-22

Part number: 8040613

FESTO



Data sheet

Feature	Value
Size	Standard
Nominal width	20 mm
Tubing insertion depth	27.54 mm
Type of seal on screwed plug	Sealing ring
Mounting position	Any
Design	Straight design
Pack size	1
Structural design	Push-pull principle
Operating pressure for entire temperature range	-0.095 MPa...1.4 MPa -0.95 bar...14 bar -13.775 psi...203 psi
Temperature-dependent operating pressure	-0.095 MPa...1.4 MPa -0.95 bar...14 bar -13.775 psi...203 psi
Information on operating pressure	Water: max. 0.6 MPa at max. 50 °C
Operating medium	Compressed air as per ISO 8573-1:2010 [7:::] Water (liquid, ice-free)
Information on operating and pilot media	Lubricated operation possible Water: G-thread only possible with sealing ring type OL as additional accessory
Corrosion resistance class (CRC)	1 - Low corrosion stress
LABS (PWIS) conformity	VDMA24364-B1/B2-L
Cleanroom suitability, measured according to ISO 14644-1	Class 4 according to ISO 14644-1
Ambient temperature	-20 °C...80 °C
Nominal tightening torque	20 Nm
Tolerance for nominal tightening torque	±20%
Product weight	91.2 g
Type of mounting	External hexagon SW32
Pneumatic connection 1	External thread G3/4
Pneumatic connection 2	for pneumatic tubing outside diameter 22 mm
Releasing ring color	Blue
Note on materials	RoHS compliant
Housing material	Brass, nickel-plated

Feature	Value
Releasing ring material	POM
Material of tubing seal	NBR
Material of tube retaining claw	high-alloy stainless steel