

Linear actuator DGPL-32- -

Part number: 175135

FESTO



Data sheet

Feature	Value
Stroke	10 mm...3000 mm
Piston diameter	32 mm
Cushioning	Pneumatic cushioning, adjustable at both ends Pneumatic shock absorber, hard characteristic curve
Mounting position	Any
Guide	Plain-bearing guide Basic guide Recirculating ball bearing Heavy-duty guide
Driver principle	Positive locking (slot)
Position sensing	Via proximity switch With linear potentiometer attached With integrated linear potentiometer
Variants	Supply port at both ends Protected version Standard slide Extended slide Rear clamping unit Clamping unit, underneath Front clamping unit
Operating pressure	0.2 MPa...0.8 MPa 2 bar...8 bar
Mode of operation	Double-acting
Explosive ambient temperature	-10°C ≤ Ta ≤ +60°C
Operating medium	Compressed air as per ISO 8573-1:2010 [7:-:-]
Information on operating and pilot media	Operation with oil lubrication possible (required for further use)
Corrosion resistance class (CRC)	0 - No corrosion stress 1 - Low corrosion stress 2 - Moderate corrosion stress
LABS (PWIS) conformity	VDMA24364-B1/B2-L
Degree of protection	IP65
Ambient temperature	-10 °C...60 °C
Cushioning length	20 mm
Theoretical force at 6 bar, retracting	483 N
Theoretical force at 6 bar, advancing	483 N
Alternative connections	See product drawing

Feature	Value
Pneumatic connection	G1/8
Cover material	Cast aluminum Coated
Seals material	NBR TPE-U(PU)
Housing material	Aluminum Anodized