

# Push-in L-connector QSL-8H-6

Part number: 153062

**FESTO**



## Data sheet

| Feature                                                   | Value                                                                     |
|-----------------------------------------------------------|---------------------------------------------------------------------------|
| Size                                                      | Standard                                                                  |
| Nominal width                                             | 3.5 mm                                                                    |
| Tubing insertion depth                                    | 17 mm                                                                     |
| Mounting position                                         | Any                                                                       |
| Design                                                    | L-shape                                                                   |
| Pack size                                                 | 10                                                                        |
| Structural design                                         | Push-pull principle                                                       |
| Operating pressure for entire temperature range           | -0.095 MPa...0.6 MPa<br>-0.95 bar...6 bar<br>-13.775 psi...87 psi         |
| Temperature-dependent operating pressure                  | -0.095 MPa...1.4 MPa<br>-0.95 bar...14 bar<br>-13.775 psi...203 psi       |
| Information on operating pressure                         | Water: max. 0.6 MPa at max. 50 °C                                         |
| Operating medium                                          | Compressed air as per ISO 8573-1:2010 [7:-:-]<br>Water (liquid, ice-free) |
| Information on operating and pilot media                  | Lubricated operation possible                                             |
| Corrosion resistance class (CRC)                          | 1 - Low corrosion stress                                                  |
| LABS (PWIS) conformity                                    | VDMA24364-B1/B2-L                                                         |
| Cleanroom suitability, measured according to ISO 14644-14 | Class 4 according to ISO 14644-1                                          |
| Ambient temperature                                       | -10 °C...80 °C                                                            |
| Product weight                                            | 5.2 g                                                                     |
| Pneumatic connection 1                                    | Push-in sleeve Ø 8 mm                                                     |
| Pneumatic connection 2                                    | for pneumatic tubing outside diameter 6 mm                                |
| Releasing ring color                                      | Blue                                                                      |
| Note on materials                                         | RoHS compliant                                                            |
| Housing material                                          | PBT                                                                       |
| Releasing ring material                                   | POM                                                                       |
| Material of tubing seal                                   | NBR                                                                       |
| Material of tube retaining claw                           | high-alloy stainless steel                                                |