

# Quick coupling plug KS4-1/2-A

Part number: 531676

**FESTO**



## Data sheet

| Feature                                              | Value                                                               |
|------------------------------------------------------|---------------------------------------------------------------------|
| Nominal width                                        | 7.85 mm                                                             |
| Operating pressure for entire temperature range      | -0.095 MPa...1.2 MPa<br>-0.95 bar...12 bar<br>-13.775 psi...174 psi |
| Normal nominal flow rate (normalized to DIN 1343)    | 756 l/min...1323 l/min                                              |
| Nominal flow rate standardized according to ISO 8778 | 819.5 l/min...1434.1 l/min                                          |
| Operating medium                                     | Compressed air as per ISO 8573-1:2010 [7:...]                       |
| Information on operating and pilot media             | Lubricated operation possible                                       |
| Corrosion resistance class (CRC)                     | 1 - Low corrosion stress                                            |
| LABS (PWIS) conformity                               | VDMA24364-B1/B2-L                                                   |
| Ambient temperature                                  | -10 °C...60 °C                                                      |
| Nominal tightening torque                            | 32.5 Nm                                                             |
| Tolerance for nominal tightening torque              | ±20%                                                                |
| Product weight                                       | 55 g                                                                |
| Pneumatic connection 1                               | External thread G1/2                                                |
| Note on materials                                    | RoHS compliant                                                      |
| Material of threaded seal                            | PA66-GF30 / TPE-U                                                   |
| Information on materials                             | Brass, nickel-plated                                                |