



# Quarter turn actuator DAPS-0180-090-RS1-F0710-MW

Part number: 8005038

**FESTO**



## Data sheet

| Feature                                         | Value                                                              |
|-------------------------------------------------|--------------------------------------------------------------------|
| Size of valve actuator                          | 0180                                                               |
| Flange hole pattern                             | F07<br>F10                                                         |
| Swivel angle                                    | 92 deg                                                             |
| Depth shaft connection                          | 24.3 mm                                                            |
| Information on the end-position adjusting range | One end position optionally adjustable                             |
| Standard connection for valve                   | ISO 5211                                                           |
| Cushioning                                      | No cushioning                                                      |
| Mounting position                               | Any                                                                |
| Mode of operation                               | Single-acting                                                      |
| Structural design                               | Kinematic yoke system                                              |
| Position sensing                                | None                                                               |
| Closing direction                               | Closes to the right                                                |
| Valve connection conforms to standard           | VDI/VDE 3845 (NAMUR)                                               |
| Safety integrity level (SIL)                    | Up to SIL 2 high demand mode<br>Up to SIL 2 low demand mode        |
| Connection pressure for spring force            | 0.28 MPa<br>2.8 bar                                                |
| Operating pressure                              | 0.28 MPa...0.84 MPa<br>2.8 bar...8.4 bar                           |
| Nominal operating pressure                      | 0.56 MPa<br>5.6 bar                                                |
| CE marking (see declaration of conformity)      | as per EU explosion protection directive (ATEX)                    |
| UKCA marking (see declaration of conformity)    | acc. to UK EX instructions                                         |
| Explosion prevention and protection             | Zone 1 (ATEX)<br>Zone 2 (ATEX)<br>Zone 21 (ATEX)<br>Zone 22 (ATEX) |
| Certificate issuing authority                   | German Technical Control Board North (TÜV Nord) 212170801          |
| ATEX category gas                               | II 2G                                                              |
| ATEX category for dust                          | II 2D                                                              |
| Type of ignition protection for gas             | Ex h IIC T6...T3 Gb X                                              |
| Type of (ignition) protection for dust          | Ex h IIIC T85°C...T200°C Db X                                      |
| Explosive ambient temperature                   | -20°C ≤ Ta ≤ +60°C                                                 |

| Feature                                                       | Value                                                              |
|---------------------------------------------------------------|--------------------------------------------------------------------|
| Operating medium                                              | Compressed air as per ISO 8573-1:2010 [7:4:4]                      |
| Information on operating and pilot media                      | Operation with oil lubrication possible (required for further use) |
| Corrosion resistance class (CRC)                              | 2 - Moderate corrosion stress                                      |
| LABS (PWIS) conformity                                        | VDMA24364-B1/B2-L                                                  |
| Ambient temperature                                           | -20 °C...80 °C                                                     |
| Spring return torque at 0° swivel angle                       | 60 Nm                                                              |
| Spring return torque with 50° swivel angle                    | 45 Nm                                                              |
| Spring return torque with 90° swivel angle                    | 90 Nm                                                              |
| Spring force                                                  | 1                                                                  |
| Air consumption at 6 bar per cycle 0°-nominal swivel angle-0° | 7 l                                                                |
| Product weight                                                | 11700 g                                                            |
| Shaft connection                                              | T22                                                                |
| Pneumatic connection                                          | G1/8                                                               |
| Note on materials                                             | RoHS compliant                                                     |
| Cover material                                                | Wrought aluminum alloy                                             |
| Seals material                                                | FPM<br>NBR<br>PUR                                                  |
| Housing material                                              | Wrought aluminum alloy                                             |
| Material of screws                                            | High-alloy steel                                                   |
| Shaft material                                                | High-alloy steel                                                   |
| Material number for shaft                                     | 1,4305                                                             |