


# Quick exhaust valve SEU-3/8-NPT

Part number: 9800

**FESTO**



## Data sheet

| Feature                                            | Value                                                              |
|----------------------------------------------------|--------------------------------------------------------------------|
| Valve function                                     | Quick exhaust                                                      |
| Selection of additional function                   | with muffler                                                       |
| Pneumatic connection 1                             | 3/8 NPT                                                            |
| Pneumatic connection 2                             | 3/8 NPT                                                            |
| Type of mounting                                   | Screw-in                                                           |
| Standard nominal flow rate exhaust air 6->5 bar    | 2280 l/min                                                         |
| Standard flow rate exhaust 6-> 0 bar               | 4680 l/min                                                         |
| Standard nominal flow rate pressurization 6->5 bar | 2880 l/min                                                         |
| Operating pressure                                 | 0.2 bar...10 bar                                                   |
| Ambient temperature                                | -20 °C...75 °C                                                     |
| Operating medium                                   | Compressed air as per ISO 8573-1:2010 [7:::]                       |
| Nominal width                                      | 11 mm                                                              |
| Information on operating and pilot media           | Operation with oil lubrication possible (required for further use) |
| LABS (PWIS) conformity                             | VDMA24364-B1/B2-L                                                  |
| Temperature of medium                              | -20 °C...75 °C                                                     |
| Noise level                                        | 83 dB(A)                                                           |
| Note on materials                                  | RoHS compliant                                                     |