

Electric linear slide EGSK-33- -

Part number: 562752

FESTO



Data sheet

Feature	Value
Working stroke	100 mm...630 mm
Size	33
Screw diameter	10 mm
Mounting position	Any
Guide	Recirculating ball bearing
Structural design	Electromechanical linear axis With ball screw
Homing	Reference switch
Spindle type	Ball screw
Max. acceleration	20 m/s ²
Max. speed	0.395 m/s...1.1 m/s
Repetition accuracy	±0.003 - ±0.01 mm
Corrosion resistance class (CRC)	0 - No corrosion stress
LABS (PWIS) conformity	VDMA24364 Zone III
Degree of protection	IP10
Ambient temperature	0 °C...40 °C
Fixed bearing dynamic basic load rating	1790 N
2nd moment of area I _y	62000 mm ⁴
2nd moment of area I _z	380000 mm ⁴
Max. feed force F _x	148 N...239 N
Mass moment of inertia J _H per meter of stroke	0.0771 kgcm ²
Feed constant	6 mm/U...10 mm/U
Statistical fixed bearing load rating	2590 N
Type of mounting	With internal thread and dowel pin
Material of end caps	Die-cast aluminum Coated
Profile material	Coated High-alloy steel
Note on materials	RoHS compliant
Drive cover material	Die-cast aluminum Coated
Slide material	Steel

Feature	Value
Ball screw nut material	Steel
Spindle material	Steel