


# Air solenoid valve VUVS-L20-P53E-MD-G18-F7

Part number: 575252

**FESTO**



## Data sheet

| Feature                                           | Value                                                                                |
|---------------------------------------------------|--------------------------------------------------------------------------------------|
| Valve function                                    | 5/3 exhausted                                                                        |
| Actuation type                                    | Electrical                                                                           |
| Valve size                                        | 21 mm                                                                                |
| Normal nominal flow rate (normalized to DIN 1343) | 600 l/min                                                                            |
| Pneumatic working port                            | G1/8                                                                                 |
| Operating pressure                                | 0.25 MPa...1 MPa<br>2.5 bar...10 bar                                                 |
| Structural design                                 | Piston gate valve                                                                    |
| Reset method                                      | Mechanical spring                                                                    |
| Certification                                     | c UL us - recognized (OL)                                                            |
| Nominal width                                     | 4.5 mm                                                                               |
| Exhaust air function                              | Adjustable                                                                           |
| Sealing principle                                 | Soft                                                                                 |
| Mounting position                                 | Any                                                                                  |
| Manual override                                   | Detenting<br>Non-detenting                                                           |
| Type of control                                   | Piloted                                                                              |
| Pilot air supply port                             | Internal                                                                             |
| Flow direction                                    | Non-reversible                                                                       |
| Lap                                               | Positive overlap                                                                     |
| b-value                                           | 0.35                                                                                 |
| C value                                           | 2.5 l/sbar                                                                           |
| Switching time off                                | 44 ms                                                                                |
| On switching time                                 | 13 ms                                                                                |
| Changeover time                                   | 24 ms                                                                                |
| Max. positive test pulse with 0 signal            | 1900 µs                                                                              |
| Max. negative test pulse on 1 signal              | 2700 µs                                                                              |
| Operating medium                                  | Compressed air as per ISO 8573-1:2010 [7:4:4]                                        |
| Information on operating and pilot media          | Operation with oil lubrication possible (required for further use)                   |
| Vibration resistance                              | Transport application test with severity level 2 as per FN 942017-4 and EN 60068-2-6 |
| Shock resistance                                  | Shock test with severity level 2 as per FN 942017-5 and EN 60068-2-27                |

| Feature                                                   | Value                                                    |
|-----------------------------------------------------------|----------------------------------------------------------|
| Corrosion resistance class (CRC)                          | 2 - Moderate corrosion stress                            |
| LABS (PWIS) conformity                                    | VDMA24364-B1/B2-L                                        |
| Cleanroom suitability, measured according to ISO 14644-14 | Class 6 according to ISO 14644-1                         |
| Temperature of medium                                     | -10 °C...60 °C                                           |
| Pilot medium                                              | Compressed air as per ISO 8573-1:2010 [7:4:4]            |
| Ambient temperature                                       | -10 °C...60 °C                                           |
| Product weight                                            | 229 g                                                    |
| Type of mounting                                          | Alternatively:<br>On terminal strip<br>With through-hole |
| Venting hole connection                                   | Not ducted                                               |
| Pilot exhaust air port 82                                 | M5                                                       |
| Pilot exhaust air port 84                                 | M5                                                       |
| Pneumatic connection 1                                    | G1/8                                                     |
| Pneumatic connection 2                                    | G1/8                                                     |
| Pneumatic connection 3                                    | G1/8                                                     |
| Pneumatic connection 4                                    | G1/8                                                     |
| Pneumatic connection 5                                    | G1/8                                                     |
| Note on materials                                         | RoHS compliant                                           |
| Seals material                                            | HNBR<br>NBR                                              |
| Housing material                                          | Die-cast aluminum<br>Painted                             |
| Piston slide material                                     | high-alloy stainless steel                               |
| Material of screws                                        | Galvanized steel                                         |