


# Air solenoid valve

## VZWF-B-L-M22C-N1-275-V-1P4-6

Part number: 1492194

**FESTO**



## Data sheet

| Feature                          | Value                                                                                                                               |
|----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| Structural design                | Diaphragm valve<br>Force pilot operated                                                                                             |
| Actuation type                   | Electrical                                                                                                                          |
| Sealing principle                | Soft                                                                                                                                |
| Mounting position                | Magnet, upright                                                                                                                     |
| Type of mounting                 | In-line installation                                                                                                                |
| Fitting connection               | 1 NPT                                                                                                                               |
| Electrical connection            | Type A<br>Plug<br>As per EN 175301-803<br>Rectangular design                                                                        |
| Nominal width                    | 27.5 mm                                                                                                                             |
| Valve function                   | 2/2-way, closed, monostable                                                                                                         |
| Manual override                  | None                                                                                                                                |
| Flow direction                   | Non-reversible                                                                                                                      |
| Medium                           | Compressed air as per ISO 8573-1:2010 [7:::]<br>Inert gas<br>Mineral oil<br>Water<br>Neutral liquids<br>Other flow media on request |
| Nominal pressure of fitting PN   | 40                                                                                                                                  |
| Pressure difference              | 0 MPa<br>0 psi                                                                                                                      |
| Differential pressure            | 0 bar                                                                                                                               |
| Coil characteristics             | 24 V DC: 11.0 W                                                                                                                     |
| Permissible voltage fluctuations | +/- 10%                                                                                                                             |
| Medium pressure                  | 0 MPa...0.6 MPa<br>0 bar...6 bar<br>0 psi...87 psi                                                                                  |

| Feature                                           | Value                      |
|---------------------------------------------------|----------------------------|
| Max. viscosity                                    | 22 mm <sup>2</sup> /s      |
| Temperature of medium                             | -10 °C...80 °C             |
| Ambient temperature                               | -10 °C...35 °C             |
| Leak rate to EN 12266-1                           | A                          |
| Flow rate Kv                                      | 11 m <sup>3</sup> /h       |
| Normal nominal flow rate (normalized to DIN 1343) | 11750 l/min                |
| On switching time                                 | 275 ms                     |
| Switching time off                                | 290 ms                     |
| Note on materials                                 | RoHS compliant             |
| LABS (PWIS) conformity                            | VDMA24364 Zone III         |
| Housing material                                  | Cast brass                 |
| Material number of housing                        | CW617N                     |
| Seals material                                    | FPM                        |
| Material of screws                                | high-alloy stainless steel |
| Material number of screw                          | 1,4301                     |
| Product weight                                    | 1500 g                     |
| Degree of protection                              | IP65                       |
| Corrosion resistance class (CRC)                  | 1 - Low corrosion stress   |