



# Air solenoid valve VSVA-B-B52-Z-A1-1T1L

Part number: 8033065

**FESTO**



## Data sheet

| Feature                                                                 | Value                                                                                                     |
|-------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|
| Valve function                                                          | 5/2-way, bistable                                                                                         |
| Actuation type                                                          | Electrical                                                                                                |
| Width                                                                   | 26 mm                                                                                                     |
| Normal nominal flow rate (normalized to DIN 1343)                       | 1100 l/min                                                                                                |
| Pneumatic working port                                                  | Sub-base, size 26 mm according to ISO 15407-1<br>Connecting plate size 01 according to VDMA 24563<br>G1/4 |
| Operating voltage                                                       | 24V DC                                                                                                    |
| Operating pressure                                                      | -0.09 MPa...1 MPa<br>-0.9 bar...10 bar                                                                    |
| Structural design                                                       | Piston gate valve                                                                                         |
| Certification                                                           | c UL us - recognized (OL)                                                                                 |
| Degree of protection                                                    | IP65<br>NEMA 4                                                                                            |
| Exhaust air function                                                    | Adjustable<br>Via throttle plate<br>Via individual sub-base                                               |
| Sealing principle                                                       | Soft                                                                                                      |
| Mounting position                                                       | Any                                                                                                       |
| Manual override                                                         | Covered                                                                                                   |
| Type of control                                                         | Piloted                                                                                                   |
| Pilot air supply port                                                   | External<br>Internal                                                                                      |
| Flow direction                                                          | Any                                                                                                       |
| Lap                                                                     | Positive overlap                                                                                          |
| Signal status display                                                   | LED                                                                                                       |
| Pilot pressure MPa                                                      | 0.3 MPa...1 MPa                                                                                           |
| Pilot pressure                                                          | 3 bar...10 bar                                                                                            |
| Flow rate of pneumatic valve                                            | 1400 l/min                                                                                                |
| Flow rate of pneumatic valve on individual sub-base                     | 1200 l/min                                                                                                |
| Optimized flow rate of pneumatic valve, pneumatically concatenated flow | 1350 l/min                                                                                                |
| Optimized flow rate of pneumatic valve pneumatically concatenated flow  | 1100 l/min                                                                                                |
| Changeover time                                                         | 18 ms                                                                                                     |

| Feature                                  | Value                                                                                |
|------------------------------------------|--------------------------------------------------------------------------------------|
| Duty cycle                               | 100%                                                                                 |
| Max. positive test pulse with 0 signal   | 1200 µs                                                                              |
| Max. negative test pulse on 1 signal     | 1100 µs                                                                              |
| Max. current consumption                 | 72 mA                                                                                |
| Nominal operating voltage DC             | 24 V                                                                                 |
| Coil characteristics                     | 24 V DC: 1.6 W                                                                       |
| Surge resistance                         | 2.5 kV                                                                               |
| Contamination level                      | 3                                                                                    |
| Permissible voltage fluctuations         | +/- 10%                                                                              |
| Operating medium                         | Compressed air as per ISO 8573-1:2010 [7:4:4]                                        |
| Information on operating and pilot media | Operation with oil lubrication possible (required for further use)                   |
| Vibration resistance                     | Transport application test with severity level 2 as per FN 942017-4 and EN 60068-2-6 |
| Shock resistance                         | Shock test with severity level 2 as per FN 942017-5 and EN 60068-2-27                |
| Corrosion resistance class (CRC)         | 0 - No corrosion stress                                                              |
| LABS (PWIS) conformity                   | VDMA24364-B1/B2-L                                                                    |
| Relative air humidity                    | 0 - 90%                                                                              |
| Pilot medium                             | Compressed air as per ISO 8573-1:2010 [7:4:4]                                        |
| Ambient temperature                      | -5 °C...50 °C                                                                        |
| Product weight                           | 276 g                                                                                |
| Electrical connection                    | Plug-in<br>As per ISO 15407-2                                                        |
| Type of mounting                         | On sub-base                                                                          |
| Pilot air port 12/14                     | Sub-base, size 26 mm as per ISO 15407-2                                              |
| Pilot exhaust air port 82/84             | Ducted<br>Not ducted as per standard<br>Alternatively:                               |
| Pneumatic connection 1                   | Sub-base, size 26 mm as per ISO 15407-2                                              |
| Pneumatic connection 2                   | Sub-base, size 26 mm as per ISO 15407-2                                              |
| Pneumatic connection 3                   | Sub-base, size 26 mm as per ISO 15407-2                                              |
| Pneumatic connection 4                   | Sub-base, size 26 mm as per ISO 15407-2                                              |
| Pneumatic connection 5                   | Sub-base, size 26 mm as per ISO 15407-2                                              |
| Note on materials                        | RoHS compliant                                                                       |
| Seals material                           | FPM<br>HNBR<br>NBR                                                                   |
| Housing material                         | Die-cast aluminum<br>PA                                                              |
| Material of screws                       | Galvanized steel                                                                     |