


ISO cylinder DSBG-...-125- -

Part number: 2045493

FESTO



Data sheet

Feature	Value
Stroke	1 mm...2800 mm
Piston diameter	125 mm
Piston rod thread	M27x2 M27 M24 M20x1.5 M20 M16x1.5 M16
Based on norm	ISO 15552
Cushioning	Elastic cushioning rings/pads at both ends Self-adjusting pneumatic end-position cushioning Pneumatic cushioning, adjustable at both ends
Mounting position	Any
Conforms to standard	ISO 15552
Piston rod end	External thread Internal thread
Structural design	Piston Piston rod Tie rod 1 Cylinder barrel
Position sensing	Via proximity switch
Variants	For unlubricated operation Protective bellows on the bearing cap Hard scraper Stroke adjustment advancing Weld spatter protection Extended external thread piston rod Internal thread on piston rod Piston rod with external hexagon Low friction for balancer applications Metal scraper Module for reaching a specific end position in case of a pressure failure Reinforced piston rod Uniform, slow movement Low friction Through, hollow piston rod Variable stud length Temperature range 0 to + 150°C Temperature range -40 to 80°C

Feature	Value
	Shortened piston rod external thread Additional PTFE piston guide
Operating pressure	0.005 MPa...1 MPa 0.05 bar...10 bar
Mode of operation	Double-acting
CE marking (see declaration of conformity)	as per EU explosion protection directive (ATEX)
UKCA marking (see declaration of conformity)	acc. to UK EX instructions
Explosion prevention and protection	Zone 1 (ATEX) Zone 1 (UKEX) Zone 2 (ATEX) Zone 21 (ATEX) Zone 21 (UKEX) Zone 22 (ATEX)
Explosion protection certification outside the EU	EPL Db (GB) EPL Gb (GB)
Operating medium	Compressed air as per ISO 8573-1:2010 [7:4:4]
Information on operating and pilot media	Operation with oil lubrication possible (required for further use)
Corrosion resistance class (CRC)	2 - Moderate corrosion stress 3 - High corrosion stress
LABS (PWIS) conformity	VDMA24364-B1/B2-L VDMA24364 Zone III
Ambient temperature	-40 °C...150 °C
Impact energy in the end positions	2.6 J...3.3 J
Cushioning length	42 mm
Theoretical force at 6 bar, retracting	6881 N
Theoretical force at 6 bar, advancing	6881 N...7363 N
Weight surcharge per 10 mm piston rod extension	63 g
Weight surcharge per 10 mm piston rod thread extension	41 g
Type of mounting	Alternatively: With internal thread With accessories
Pneumatic connection	G1/2
Note on materials	RoHS compliant
Cover material	Die-cast aluminum, coated
Piston seal material	FPM HNBR TPE-U(PU)
Material of piston	Wrought aluminum alloy
Piston rod material	high-alloy stainless steel, hard chrome plated High-alloy steel high-alloy stainless steel
Piston rod wiper material	FPM HNBR Protective grounding TPE-U(PU)
Buffer seal material	FPM
Material of cylinder barrel	Wrought aluminum alloy, smooth-anodized
Nut material	Steel, galvanized high-alloy stainless steel
Material of bearing	Bronze Metal polymer compound POM
Tie rod material	High-alloy steel high-alloy stainless steel