

Pneumatic valve VUWS-25

Part number: 8022015

FESTO



Data sheet

Feature	Value
Valve function	2x3/2 closed, monostable 2x3/2 open monostable 2x3/2, open/closed, monostable 3/2-way, closed, monostable 3/2-way, monostable, open 5/2-way, bistable 5/2-way, monostable 5/3-way, pressurized 5/3 exhausted 5/3-way, closed
Actuation type	Pneumatic
Valve size	26.5 mm
Normal nominal flow rate (normalized to DIN 1343)	1000 l/min...1300 l/min
Pneumatic working port	G1/4 1/4 NPT QS-6 QS-8 QS-10 QS-1/4 QS-5/16 QS-3/8
Operating pressure	-0.9 bar...10 bar
Structural design	Piston gate valve Plate seat
Reset method	Mechanical spring Pneumatic spring
Certification	c UL us - recognized (OL)
Exhaust air function	Adjustable
Sealing principle	Soft
Mounting position	Any
Manual override	None
Type of control	directly
Explosion prevention and protection	Observe the information on the certificate Zone 1 (ATEX) Zone 2 (ATEX) Zone 21 (ATEX) Zone 22 (ATEX)
Operating medium	Compressed air as per ISO 8573-1:2010 [7:4:4]

Feature	Value
Information on operating and pilot media	Operation with oil lubrication possible (required for further use)
Corrosion resistance class (CRC)	2 - Moderate corrosion stress
LABS (PWIS) conformity	VDMA24364-B1/B2-L
Cleanroom suitability, measured according to ISO 14644-14	Class 6 according to ISO 14644-1
Pilot medium	Compressed air as per ISO 8573-1:2010 [7:4:4]
Type of mounting	Alternatively: On terminal strip With through-hole
Venting hole connection	Not ducted
Note on materials	RoHS compliant
Housing material	Die-cast aluminum Painted
Material of screws	Galvanized steel