


# Round cylinder DSNU-40-160-PPV-A

Part number: 196036

**FESTO**



## Data sheet

| Feature                                  | Value                                                              |
|------------------------------------------|--------------------------------------------------------------------|
| Stroke                                   | 160 mm                                                             |
| Piston diameter                          | 40 mm                                                              |
| Piston rod thread                        | M12x1.25                                                           |
| Cushioning                               | Pneumatic cushioning, adjustable at both ends                      |
| Mounting position                        | Any                                                                |
| Structural design                        | Piston<br>Piston rod<br>Cylinder barrel                            |
| Position sensing                         | Via proximity switch                                               |
| Operating pressure                       | 0.1 MPa...1 MPa<br>1 bar...10 bar                                  |
| Mode of operation                        | Double-acting                                                      |
| Operating medium                         | Compressed air as per ISO 8573-1:2010 [7:4:4]                      |
| Information on operating and pilot media | Operation with oil lubrication possible (required for further use) |
| Corrosion resistance class (CRC)         | 2 - Moderate corrosion stress                                      |
| LABS (PWIS) conformity                   | VDMA24364-B1/B2-L                                                  |
| Ambient temperature                      | -20 °C...80 °C                                                     |
| Impact energy in the end positions       | 0.7 J                                                              |
| Cushioning length                        | 18 mm                                                              |
| Theoretical force at 6 bar, retracting   | 633.3 N                                                            |
| Theoretical force at 6 bar, advancing    | 752.9 N                                                            |
| Moving mass                              | 486 g                                                              |
| Product weight                           | 1045 g                                                             |
| Type of mounting                         | With accessories                                                   |
| Pneumatic connection                     | G1/4                                                               |
| Note on materials                        | RoHS compliant                                                     |
| Cover material                           | Wrought aluminum alloy                                             |
| Seals material                           | NBR<br>TPE-U(PU)                                                   |
| Piston rod material                      | High-alloy steel                                                   |
| Material of cylinder barrel              | high-alloy stainless steel                                         |