




**SERIES NAVE
PLUG**
CODE 467051



Datasheet

Electrical characteristics

Rated current	10A
Supply Voltage	127V~ 50/60Hz
Poles	2P+ $\frac{1}{2}$
Clock Position	-
Rated insulation voltage	-
Signal plug inserted	-

Reference Standards and Directives

Certification and approval marks	
Directives	2011/65/EU (RoHS), 2012/19/EU (WEEE)
Reference Standards	EN 60529:1991, EN 60529:1991/A1:2000, EN IEC 63000:2018, UNAV 1437

Mechanical characteristics

Manufacturing material	Elastomer
Alveolus/plugs treatment	-
Color	-
Tightening diameter	12 mm
Execution	Mobile
IP Protection degree	IP56
Additional IPdegree protection	-
Shock resistance	IK10 according to IEC/EN 62262
Resistance to Glow wire	-
Flame rating according UL94	-
Terminals type	Screw - indirect clamping
Conductors section (Cu)	Min: 1 mm ² ;Max: 2.5 mm ²
Terminal tightening torque	1,2 Nm
Net Weight	0.17 KG
Working Environment Temp.	Min: -40°C ;Max: +70°C
Warehousing Temperature	Min: -50°C ;Max: +80°C

The images are purely indicative. Palazzoli reserves the right to make changes without notice.