




SERIES CAM
CMP_INT
CODE 292542



Datasheet

Electrical characteristics

Rated current	125A
Supply Voltage	690V~ 50/60Hz
Poles	3P
Rated insulation voltage	690 V
Insulation Class	II
CAM layout	2
Function Apparatus Control	One way switches
Type of protection	None

Mechanical characteristics

Manufacturing material	Palazzoli Thermosetting GRP
Treatment type	-
Surface finishing	-
Color	RAL 7042 (Base), Blue RAL 5015 (Cover)
Execution	Wall mounting
Dimensions	250X185X206 mm
Depth	-
Front-plate dimension	-
Hole type	Window type A
IP Protection degree	IP65
Additional IPdegree protection	-
Shock resistance	IK10 according to IEC/EN 62262
Resistance to Glow wire	960°C
Flame rating according UL94	V-0
Corrosivity category	-
Net Weight	3.2 KG
Working Environment Temp.	Min: -25°C ;Max: +60°C
Warehousing Temperature	Min: -50°C ;Max: +80°C

Technical data switch

Thermal current	125 A
Rated short-circuit current	16,5 kA
Terminals type	Screw - indirect clamping
Conductors section (Cu)	Min: 10 mm ² ;Max: 70 mm ²
Terminal tightening torque	6 Nm
Auxiliary status contacts	Max 2 (optional)
Padlockable handle	2 locks Ø4,5 mm max

Operating category

a	Tensione	Corrente / Potenza
Rating	Voltage	Current / Power
AC-22A	230 V	125 A
	400 V	125 A
	500 V	125 A
	690 V	125 A
AC-23A	230 V	90 A
	400 V	90 A
	500 V	70 A
	690 V	50 A
AC-23A	230 V	22 kW
	400 V	45 kW
	500 V	45 kW
	690 V	45 kW

Reference Standards and Directives

Certification and approval marks UKCA, CE

Directives 2011/65/EU (RoHS), 2012/19/EU (WEEE), 2014/35/EU (LVD)

Reference Standards EN 60947-1:2007, EN 60947-1:2007/A1:2011, EN 60947-1:2007/A2:2014, EN 60947-3:2009, EN 60947-3:2009/A1:2012, EN 60947-3:2009/A2:2015, EN IEC 63000:2018

The images are purely indicative. Palazzoli reserves the right to make changes without notice.